



- Note : 1) \*\*Dimensions for reference only  
 2) Tags material to be isotan (44% Ni, 1% Mn, Rest Cu)  
 3) #Tag to be level with surface A with in  $\pm 0.15$  mm  
 4) \*Dimensions to be controlled at incoming material & verify by QC  
 5) \*\*\*VARTA marking orientation only for reference, these marking may be covered. Approx. wt : 4 g

No	AO No	Revision	Date	Name
5	16-R069	Added note no. 5	2016-05-10	Jadi
4	16-R232	Use new cell with Baby symbol	2016-04-28	Jadi
3	15-R015	Change solder tags from without buckle to with buckle	2015-01-27	Jadi
2	C091/05	Change to protrusions to 14.7mm from center cell was 5.7mm from edge of cell & remove kapton tape	2005-09-16	Ratna
1	C063/04	Add kapton tape to prevent any short circuit & add spec for bent tag	2004-10-14	Ratna
0	T053/04	Refer to provisional drawing #P01-00037 Rev. 000	2004-08-31	Ratna

Projection :		Material : Refer to part list no: 074695		Description : <b>CR 2032 FM</b> with solder tags	
Dimension in mm	Prepare & Checked	Verified & Approval		Dwg. No :	074695
Tolerance : As specified	2004-08-27	Ratna		VKB Order No. :	06032 101 032
Scale : 2 : 1					4 0 5