

LogiLink®

4K x 2K HDMI Audio Extractor Converter

Art. No.: CV0106


Experience 4K video with high-quality 2CH/5.1CH audio. Perfect for home theatre.

Features:

- » HDMI Input, HDMI + Digital SPDIF/ Analog 3.5mm Audio Output
- » Compliant with HDMI 1.4 standard, resolution up to 4K x 2K@30Hz
- » Support 300MHz/3Gbps per channel (9Gbps all channels) bandwidth
- » Support video resolutions up to 8-bit 4K (30 Hz), 12-bit 1080p (60 Hz) or 12-bit 720p/1080i (60 Hz)
- » Support 3D formats up to 300 MHz
- » Compliant with HDCP 1.4 specification
- » Support uncompressed audio such as LPCM
- » Supports compressed audio such as 2.0CH audio, 5.1CH Dolby Digital, DTS Digital
- » Powered from Micro USB (not included)







^{*}Support DTS Audio and Dolby digital audio but not Dolby Digital Plus audio.

^{*}Do not support copyright protected content.









LogiLink_®

4K x 2K HDMI Audio Extractor Converter

Art. No.: CV0106

Specification:

Input Connector	HDMI
Output Connector	HDMI
Other Connectors	Toslink/Stereo Micro USB: for charging
Input Resolutions	Up to 4K x 2K@30Hz
Output Resolutions	Up to 4K x 2K@30Hz
External Power Supply	Powered from Micro USB
Max. Power Consumption	2W
Operating Temperature	0°C ~70°C
Operating Humidity	$10\% \sim 85\%$ RH (no condensation)
Storage Temperature	-10°C ~80°C
Storage Humidity	5% ~ 90% RH (no condensation)
Dimension	55 x 55 x 16mm
Weight	55g
Cable Length	142mm













Package Contents:

- » 1 x 4K x 2K HDMI Audio Extractor Converter
- » 1 x User Manual

Package Informations:

- » Packing Dimension: 105 x 163 x 20mm
- » Packing Weight: kg
- » Carton Dimension: 460 x 340 x 185mm
- » Carton Q'ty: 60pcs» Carton Weight: kg







