

# DIGITUS Professional Line-Interactive UPS, 1000 VA/600 W

DN-170024-1  
EAN 4016032345107



## DIGITUS Line-Interactive UPS, 1000VA/600W 12V/7Ah x2 battery, 4x CEE 7/7, AVR, USB, RS232, RJ11/RJ45, LCD display

The DIGITUS® Line-Interactive UPS come with a compact size and an excellent microprocessor control, which guarantees high reliability. With an user friendly operation they provide high performance protection for your business and office computer systems against data loss and damage. Features like overload-, discharge and overcharge protection, cold start functions and energy saving features, as well as an acoustic alarm system are just a few advantages of the DIGITUS® Line-Interactive UPS units. You can download the mangement software under following link:  
<http://www.power-software-download.com/viewpower.html>

- Excellent micro process management guarantees a high reliability in case of electricity failure
- Auto restart while AC is recovering
- Cold start function
- USB/RS232 communication terminal and RJ11/45 telephone protection
- Connection Type: 4x safety outlets, 2x RJ11/RJ45, 1x RS232, 1x USB 2.0 Typ B
- Input voltage: 230 VAC
- Voltage range: 162-290 VAC
- Frequency range: 50 Hz (auto sensing)
- Output voltage: 230 VAC ± 10%
- AC voltage regulation (battery mode): 10%
- Capacity: 1000 VA/600 W
- Frequency range (battery mode): 50 Hz ± 1%
- Typical transfer time: 2-6 ms
- Waveform (battery mode): Simulated sine wave
- Battery: 12V/7Ah x 2
- Typical recharge time: 4 hours to recover 90% of capacity
- Alarm sounds: Battery mode (sounding every 10 sec.), low battery (sounding every second), overload (sounding every 0.5 seconds), fault (continuously sounding)

- Humidity: 0-90% RH @ 0 °C to +40 °C (non condensing)
- Noise level: Less than 40 dB
- With overload-, discharge-, and overcharge protection
- Boost and buck AVR for voltage stabilization
- Dimensions (HxWxD): 160x350x146 mm
- Net weight: 8.0 kg
- ViewPower software link:  
<http://www.power-software-download.com/viewpower.html>
- Input voltage: 162 V ... 290 V
- Primary frequency: ... 50 Hz
- Output voltage: 162 V ... 290 V
- Output effective power: 600 W
- Output apparent power: 1000 VA
- Output apparent power: 1000 VA
- Type of interface: Other
- SNMP: no
- Voltage type: AC
- Height: 160 mm
- Width: 350 mm
- Transition time for full load: 0.5 min
- Depth: 146 mm
- Weight: 8 kg
- Network-management: yes
- USV- technology: Line-interactive
- Construction type: Free standing model
- Max. voltage distortion output (linear load): 10 %
- Potential free switch contact: no
- Auto shut down function: no
- Input connection: Protective contact (SCHUKO)
- Number of output connections C13: 0
- Number of output connections C19: 0
- Number of output connections with protective contact (SCHUKO): 4
- Number of output connections fixed connection: 0

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm <sup>3</sup>
Packaging Unit Carton	1	8.90	44.50	19.50	25.50	22,127.60
Packaging Unit Inside	1	8.90	44.50	19.50	25.50	22,127.60
Packaging Unit Single	1	8.90	44.50	19.50	22.50	19,524.40
Net single without Packaging	1	0.00	0.00	0.00	0.00	0.00

More images:

