



ES Rectangle . RS
10.4~49.4W

LED Module maximum operating temperature(Tc) <105°C

BXRA-xxx0800/0950/1100 (10.4W)
BXRA-xxx1200/1350/1600 (14.8W)
BXRA-xxx2000/1350/2600 (25.9W)
BXRA-xxx3500/4000/4500-F-00 (31.8W)
BXRA-xxx4000/4500/5300-H-00 (49.4W)

CL-L340
47.3W

LED Module maximum operating temperature(Tc) <100°C

CL-L340-MC41N1-C1 (47.3W)
CL-L340-MC41W1-C (47.3W)
CL-L340-MC41WW1-C (47.3W)
CL-L340-MC41L1-C (47.3W)
CL-L340-MC41L2-C (47.3W)
CL-L340-C41N-C (47.3W)

PrevaLED
11.5~51.6W

LED Module maximum operating temperature(Tc) <85°C

PL-CORE-Z3-1000 (11.5W)
PL-CORE-Z3-2000 (21.4W)
PL-CORE-Z3-3000 (32.5W)
PL-CORE-Z3-5000 (51.6W)

Fortimo SLM
23~45W

LED Module maximum operating temperature(Tc) <75°C

2000lm G3 (23W)
3000lm G3 (33W)
4000lm G3 (45W)
4500lm G3 (45W)

TALEXX
21.5~41.0W

LED Module maximum operating temperature(Tc) <90°C

STARK-SLE-G3-19-2000-SEL (21.5 W)
STARK-SLE-G3-19-3000-SEL (32.5 W)
STARK-SLE-G3-23-3000-SEL (30.0 W)
STARK-SLE-G3-19-2000-SEL (40.9 W)
STARK-SLE-G3-23-4000-SEL (41.0 W)

LUGA Shop
28.8~54.4W

LED Module maximum operating temperature(Tc) <85°C

WU-M-461 (28.8W)
WU-M-462 (42.0W)
WU-M-464 (54.4W)



Size : Ø86 x 30.4mm	Size : Ø86 x 45.4mm	Size : Ø86 x 52.4mm
LA001-018A81DY (aluminum colour 5V) LA001-018B81DY (black 5V) LA001-019A81DY (aluminum colour 12V) LA001-019B81DY (black 12V)	LA004-024A83DY (aluminum colour 5V) LA004-024B83DY (black 5V) LA004-025A83DY (aluminum colour 12V) LA004-025B83DY (black 12V)	LA006-006A83DY (aluminum colour 5V) LA006-006B83DY (black 5V) LA006-007A83DY(aluminum colour 12V) LA006-007B83DY(black 12V)
Weight (g) 112 Fan Speed (RPM) 2200 Noise @ 1M , (dB(A)) 17.0	Weight (g) 194 Fan Speed (RPM) 2200 Noise @ 1M , (dB(A)) 17.0	Weight (g) 234 Fan Speed (RPM) 2200 Noise @ 1M , (dB(A)) 17.0
Zhaga hole : Book3	Zhaga hole : Book3	Zhaga hole : Book3



ES Rectangle RS
85.4W

LED Module maximum operating temperature (Tc) <105°C

BXRA-XXX7000/7500/9000-J-00 (85.4W)



Size : 121 x 92.3 x 66.0 mm
LM310-003A99DN
Weight (g) 352
Fan Speed (RPM) 2200
Noise @ 1M , (dB(A)) 17.8



COB
10.9~42.9W

LED Module maximum operating temperature (Tc) <100°C

CLL032-1205A5 (10.9W) CLL032-1208A5 (17.4W)
CLL032-1205A5 (26.8W) CLL032-1208A5 (42.9W)
CLL032-1206A5 (13.0W) CLL032-1212A5 (26.1W)
CLL032-1206A5 (32.2W) CLL042-1218A5 (39.1W)



Size : Ø86 x 40.4mm
LA003-014A82DN (aluminum colour 12V) LA003-014B82DN (black 12V)
Weight (g) 163
Fan Speed (RPM) 2200
Noise @ 1M , (dB(A)) 16.5



COB
89.3~177.9W

LED Module maximum operating temperature (Tc) <100°C

CLL044-1212 (89.3W)
CLL044-1812 (134W)
CLL044-1818 (86.7W)
CLL044-1818 (128.1W)
CLL054-1825 (120.4W)
CLL054-1825 (177.9W)



Size : 121 x 92.3 x 66.0 mm
LM310-001A99DN
Weight (g) 352
Fan Speed (RPM) 2200
Noise @ 1M , (dB(A)) 17.8



Partner Infusion
13.5~40W

LED Module maximum operating temperature (Tp) <65°C

Gen3 M1000 Series (13.5W)
Gen3 M1500 Series (20W)
Gen3 M2000 Series (27W)
Gen3 M3000 Series (40W)



Size : Ø86x40.4mm
LA003-013A82DY (Aluminum colour 5V) LA003-013B82DY (Black 5V) LA003-012A82DY (Aluminum colour 12V) LA003-012B82DY (Black12V)
Weight (g) 163
Fan Speed (RPM) 2200
Noise @ 1M , (dB(A)) 16.5



Size : Ø86x57.4mm
LA004-017A83DY (Aluminum colour 12V) LA004-017B83DY (Black 12V)
Weight (g) 268
Fan Speed (RPM) 2200
Noise @ 1M , (dB(A)) 15.9



Fortimo SLM
23~33W

LED Module maximum operating temperature (Tc) <75°C

2000lm Gen3 (23W)
3000lm Gen3 (33W)



Size : Ø99 x 110mm
SM203-13002
Weight (g) 211
AL1050
Heat Sink Material ADC10
C1100
*1 TDP (W) 23.8
*2 Thermal Resistance (°C/W) 1.38
ΔT (°C) 32.9
Zhaga hole : Book3

*1 TDP (Thermal Design Power) is for reference only. Actual thermal performance may vary by different applications. Please test it again by using on different applications.

*2 Thermal resistance is measured from the bottom middle of heat sink in free air without airflow obstructions, with PHILIPS(Fortimo LED SLM 3000 33W/930 L19 G3) LED chip.

LED Lighting Active Cooling Module & Cooling Fan

Application : MR16



Specifications	EF30080S2-E00U-A99	HA30101V3-E00U-A99
Model No.	EF30080S2-E00U-A99	HA30101V3-E00U-A99
Module Dimension (mm)	φ 30 x 8	φ 39.8 x 10.4
Weight (g)	4.3	7.3
Rated Voltage (V)	3.3/5	12
Power Consumption (W)	0.20 / 0.40	0.30
Fan Speed (RPM)	4300 / 7000	4400
Air Flow (CFM)	1.8 / 3.0	1.9
Static Pressure (Inch-H ₂ O)	0.03 / 0.08	0.04
Noise @ 1M (dB(A))	3.1 / 17.0	10.5
Safety	UL / CUR / TUV / CE	UL / CUR / TUV / CE

Application : A19



Specifications	HA40101V3-E00U-A99
Model No.	HA40101V3-E00U-A99
Module Dimension (mm)	φ 48.9 x 10.6
Weight (g)	11.8
Rated Voltage (V)	12
Power Consumption (W)	0.32
Fan Speed (RPM)	3900
Air Flow (CFM)	4.5
Static Pressure (Inch-H ₂ O)	0.05
Noise @ 1M (dB(A))	13.1
Safety	UL / CUR / TUV / CE

Cooling Fan

Application : Spotlight / Downlight



Specifications	HA60150V3-E03U-A99	HA60151V3-E00U-A99	HA60150V3-E02U-A99	HA60151V3-E01U-A99
Fan Dimension (mm)	φ 84.9 x 15.4	φ 84.9 x 15.4	φ 84.9 x 15.4	φ 84.9 x 15.4
Weight (g)	29.1	29.1	27.3	27.3
Rated Voltage (V)	5	12	5	12
Power Consumption (W)	0.26	0.28	0.40	0.34
Fan Speed (RPM)	2300	2300	2300	2300
Air Flow (CFM)	9.7	9.7	13.2	13.2
Static Pressure (Inch-H ₂ O)	0.03	0.03	0.03	0.03
Noise @1M (dB(A))	15.4	15.4	16.1	16.1
Safety	UL / CUR / TUV / CE	UL / CUR / TUV / CE	UL / CUR / TUV / CE	UL / CUR / TUV / CE

* model with PWM control function



Specifications	HA60150V3-E00U-H99 *	HA60151V3-E05U-H99 *	HA60200V3-E00U-A99	HA60201V3-E00U-A99
Model No.	HA60150V3-E00U-H99 *	HA60151V3-E05U-H99 *	HA60200V3-E00U-A99	HA60201V3-E00U-A99
Fan Dimension (mm)	φ 84.9 x 15.4	φ 84.9 x 15.4	φ 84.9 x 20.4	φ 84.9 x 20.4
Weight (g)	28.8	28.8	30.5	30.5
Rated Voltage (V)	5	12	5	12
Power Consumption (W)	0.33	0.42	0.31	0.34
Rated Speed (RPM)	2300	2300	2300	2300
Air Flow (CFM)	13.2	13.2	13	13
Static Pressure (Inch-H ₂ O)	0.03	0.03	0.03	0.03
Noise @1M (dB(A))	16.1	16.1	17.5	17.5
Safety	UL / CUR / TUV / CE	UL / CUR / TUV / CE	UL / CUR / TUV / CE	UL / CUR / TUV / CE

LED Lighting Passive Cooling Module



Specifications	SM203-13002
Model No.	SM203-13002
Module Dimension (mm)	φ 99 x 110
Weight (g)	211
Heat Sink Material	AL1050 + ADC10 + C1100
*1 TDP (W)	23.8
*2 Thermal Resistance (°C/W)	1.38
ΔT (°C)	32.9

*1: TDP (Thermal Design Power) is for reference only. Actual thermal performance may vary by different applications. Please test it again by using on different applications.

*2: Thermal resistance is measured from the bottom middle of heat sink in free air without airflow obstructions, with PHILIPS(Fortimo LED SLM 3000 33W/930 L19 G3) heat source.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [DC Fans](#) category:

Click to view products by [Sunon](#) manufacturer:

Other Similar products are found below :

[614R](#) [6424/2HP-210](#) [8312R](#) [DV4118/2NP-183](#) [AFB0948HH-S687](#) [PFB0824DHE-8B72](#) [G2E085-AA05-10](#) [RD20S-4/210660](#) [4318/12T](#)
[4418HH](#) [AUB0912H-F00](#) [3412N/2ME](#) [K2E225-RA92-09](#) [4184N/2XR](#) [5214N2HH](#) [614J2HHPR-010](#) [8412NGL-12](#) [4114N/12HHR-297](#)
[4656](#) [ZWR-903](#) [4112N12GL-175](#) [KD2406PKB2.\(2\).GN](#) [AFB1248HHE](#) [AFB1212LE-F00](#) [FAN-SCH-1](#) [MF60151V1-1000U-G99](#)
[PF80252V1-1000U-G99](#) [PF92252V1-1000U-G99](#) [4112N/2H6P](#) [4114N/17-251](#) [6212NH](#) [622/2N](#) [712F-011](#) [8218J/2NP-181](#) [W1G180-AB47-](#)
[15](#) [FAA1-12038NBKW31-A](#) [6318N/2TDP](#) [6318N/2H3PU](#) [6318HU](#) [424JMU](#) [PMD1206PTVX-A.U.GN](#) [PF80251B2-000U-F99](#)
[EF40101BX-1000U-G99](#) [AD1224LB-A71GL](#) [9GA0924L4021](#) [9GA0924M4021](#) [9GA0924M4011](#) [9GA0824B20011](#) [9GA0812A2D0011](#)
[9GA0912M4D011](#) [9GA0924W4D01](#)