

# METAL CONTROL STATIONS



 **Lovato**  
**electric**

ENERGY AND AUTOMATION

### Without actuators



LPZ M1 A5



LPZ M1 A5P



LPZ M1 A8



LPZ M2 A5



LPZ M2 A8



LPZ M3 A8



LPZ M4 A8



LPZ M5 A8



LPZ M6 A8

Order code	Description	Cover colour	Qty per pkg.	Wt.
			n°	[kg]
LPZ M1 A5	For 1 actuator	Yellow	1	0.343
LPZ M1 A5P	For 1 actuator with shroud	Yellow	1	0.382
LPZ M1 A8	For 1 actuator	Grey	1	0.349
LPZ M2 A5	For 2 actuators	Yellow	1	0.456
LPZ M2 A8	For 2 actuators	Grey	1	0.458
LPZ M3 A8	For 3 actuators	Grey	1	0.603
LPZ M4 A8	For 4 actuators	Grey	1	0.581
LPZ M5 A8	For 5 actuators	Grey	1	0.680
LPZ M6 A8	For 6 actuators	Grey	1	0.671

### General characteristics

Control stations made by aluminium alloy suitable for pushbuttons, selector switches and pilot lights Platinum and 8LM series. Maximum 3 contacts for operator (with mounting adapter) mounted on the cover.

### Operational characteristics

- Cable entry: Ø21mm (for M20 or PG13.5 cable gland)
- Degree of protection:
  - IEC/EN: IP66 and IP67
  - UL: NEMA 4X
- Earth connection through threaded holes on the base and on the cover (screws supplied)
- Ambient conditions:
  - Operating temperature: -25...+70°C
  - Storage temperature: -40...+85°C.

### Certifications and compliance

Certifications obtained: cULus.  
Compliant with standards: IEC/EN 60947-5-1.

### Dimensions

