



*DC COMPONENTS CO., LTD.*

RECTIFIER SPECIALISTS

**MB1505  
THRU  
MB1510**

**TECHNICAL SPECIFICATIONS OF SINGLE-PHASE SILICON BRIDGE RECTIFIER**

**VOLTAGE RANGE - 50 to 1000 Volts**

**CURRENT - 15 Amperes**

**FEATURES**

- \* Metal case for Maximum Heat Dissipation
- \* Surge overload ratings - 240 Amperes
- \* Low forward voltage drop

**MECHANICAL DATA**


- \* Case: Molded plastic with heatsink
- \* Epoxy: UL 94V-0 rate flame retardant
- \* Terminals: Plated .25"(6.35mm) Faston lugs, Solderable per MIL-STD-202E, Method 208 guaranteed
- \* Polarity: As marked
- \* Mounting position: Any
- \* Weight: 30 grams approx.

**MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS**

Ratings at 25 °C ambient temperature unless otherwise specified.  
Single phase, half wave, 60 Hz, resistive or inductive load.  
For capacitive load, derate current by 20%.



**MB-25**



Dimensions in inches and (millimeters)

	SYMBOL	MB1505	MB151	MB152	MB154	MB156	MB158	MB1510	UNITS
Maximum Recurrent Peak Reverse Voltage	V <sub>RRM</sub>	50	100	200	400	600	800	1000	Volts
Maximum RMS Bridge Input Voltage	V <sub>RMS</sub>	35	70	140	280	420	560	700	Volts
Maximum DC Blocking Voltage	V <sub>DC</sub>	50	100	200	400	600	800	1000	Volts
Maximum Average Forward Rectified Output Current at T <sub>c</sub> = 50°C	I <sub>o</sub>	15							Amps
Peak Forward Surge Current 8.3 ms single half sine-wave superimposed on rated load (JEDEC Method)	I <sub>FSM</sub>					300			Amps
Maximum Forward Voltage Drop per element at 5.0A DC	V <sub>F</sub>					1.1			Volts
Maximum DC Reverse Current at Rated	I <sub>R</sub>					10			μAmps
DC Blocking Voltage per element						500			
I <sup>2</sup> t Rating for Fusing (t<8.3ms)	I <sup>2</sup> t					374			A <sup>2</sup> Sec
Typical Junction Capacitance (Note1)	C <sub>J</sub>					40			pF
Typical Thermal Resistance (Note 2)	R <sub>θJA</sub>					19			°C/W
Operating and Storage Temperature Range	T <sub>J</sub> , T <sub>STG</sub>					-55 to +175		°C	

NOTES : 1.Measured at 1 MHZ and applied reverse voltage of 4.0 volts

2.Thermal Resistance from Junction to Ambient and from Junction to Lead mounted on P.C.B. with 0.47 x 0.47" (12 x 12mm) copper pads.

# RATING AND CHARACTERISTIC CURVES (MB1505 THRU MB1510)

FIG. 1 - MAXIMUM NON-REPETITIVE FORWARD SURGE CURRENT




FIG. 2 - TYPICAL FORWARD CURRENT DERATING CURVE




FIG. 3 - TYPICAL INSTANTANEOUS FORWARD CHARACTERISTICS





FIG. 4 - TYPICAL REVERSE CHARACTERISTICS



DC COMPONENTS CO., LTD.