



Approval	 	
<b>Capability</b>	<b>UL</b>	<b>IEC</b>
Standard	600V	800V
Rated Voltage	50A	41A
Rated Current	Wire size	0.2-6.0mm <sup>2</sup>
Wire size	24-8AWG	
T/W/End plate	6.2/42.5/1.6mm	
Height(mm)(NS35:7.5/NS35:15/NS32)	47/54.5/52mm	
Rated surge voltage/Contamination Class	8KV/3	
Stripping length	10mm	
Screw thread/Tightening torque	M4/1.2N.m/10.5Lb-in	
Internal cylindrical gage	A5	
Insulating Material/Inflammability class	PA/V-0	
<b>Specification</b>	<b>Model</b>	<b>Pieces</b>
(1) Terminal block	PC 6	50
(2) End cover	D-PC 2.5	50
(3) Fixed bridge	FBI 2-8	150
2-P	FBI 3-8	50
3-P	FBI 5-8	10
5-P	FBI 10-8	10
10-P		
(4) Step bracket		
(5) Insertion bridge	EB 2-8	100
2-P	EB 3-8	100
3-P	EB 10-8	50
10-P		
(6) Isolator bridge bar, 10P	ISSBI 10-8	10
(7) Bridge bar isolator	IS-K10	100
(8) Switching bridge	SB 2-8/13N	1
(9) Separating plate	TS-K	1000
(10) Separating plate, width 1.5mm	ATP-PC	50
(11) Test plug socket	DSB 4/7/6	100
(12) Test plug socket insulated	DSBJ 4/15/6	
(13) Zack strip	ZB8	300

### HOW TO ORDER :

-  **P** -  - 

X	X	X
---	---	---

  
Customer Request

Series No.

No. of pole

Color

1	Gray	4	Green	7	Trans-parent
2	Blue	5	Orange	8	Yellow
3	Black	6	Red	9	White

 mm (INCH)	 <b>DEGSON ELECTRONICS CO., LTD.</b>
 THROANGLE PROJECTION	<b>NAME</b> <b>PC 6</b>