

RHT510 Hygro-Thermometer Psychrometer



Conveniently check the Humidity and Temperature conditions in residential and professional settings to ensure comfort and safety. The RHT510 is a Hygro-Thermometer Psychrometer that measures Relative Humidity, Temperature, Dew Point, and Wet Bulb. General purpose bead wire Type K probe is included for measuring Temperature up to ~480°F (250°C), while the meter can measure to 2372°F (1300°C) if used with other probes. Min/Max function stores and recalls highest and lowest readings. Additional features include: large LCD display with backlight, Data Hold and Auto power off with disable option.



Features

- Measures Temperature (Air/Type K), Relative Humidity, Wet Bulb, and Dew Point
- Backlit LCD to view in dimly lit areas
- Data Hold and Min/Max functions
- Auto power off with disable
- Tripod mount (optional TR100 Tripod sold separately)
- Complete with wrist strap, general purpose Type K bead wire Temperature probe, and 3 AAA batteries

Specifications	Range	Max Resolution	Basic Accuracy
Temperature (Air)	32 to 122°F (0 to 50°C)	0.1°	±2.5°F (1.2°C)
Temperature (Type K)	-148°F to 2372°F (-100°C to 1300°C)	0.1°	±0.4% + 1.8°F (1°C)
Relative Humidity	10 to 95%RH	0.1%RH	±4%RH
Wet Bulb	22.2 to 120°F (-5.4 to 49.0°C)	0.1°	calculated
Dew Point	-13.5 to 120.0°F (-25.3 to 49.0°C)	0.1°	calculated
Dimensions	6 x 2.3 x 1" (153 x 58 x 25mm)		
Weight	5.6oz (160g)		

Ordering

RHT510..... Hygro-Thermometer Psychrometer
 TR100 Tripod
 TP870 Type K Bead Wire Temperature Probe (-40 to 482°F/-40 to 250°C)
 Visit extech.com and go to accessories category for more temperature probe options



UPC Code: 793950441510

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Environmental Test Equipment](#) category:

Click to view products by [Extech](#) manufacturer:

Other Similar products are found below :

[CW40](#) [F150C10E3DRT](#) [F150LTC20](#) [F150CD10E2](#) [F150L75](#) [F150LRS](#) [S-11](#) [FLUKE-LDG](#) [382153](#) [FM100](#) [RH210](#) [382253](#) [MO290-P](#)
[GEO-CABLE-REEL-50M](#) [T197914](#) [RD300-L](#) [IR11BD](#) [IR11GM](#) [IR12GM](#) [IR21BD](#) [IR31CE](#) [IR32BC](#) [IR33BC](#) [MP7217TC](#) [NGM-1](#) [SGX-](#)
[7NH3](#) [UT381](#) [F150-SLC50](#) [AW-CO-1000](#) [AW-NmHc-100](#) [3.000.401](#) [AX-7535](#) [CS-9S6SS-A](#) [P 2800 A](#) [P 2801](#) [P 2802](#) [P 5039](#) [P 5130](#) [P](#)
[5055](#) [P 5060](#) [P 5065](#) [P 5086](#) [P 5090](#) [P 5110](#) [P 5115](#) [P 5135](#) [P 5140](#) [P 5145](#) [P 5150](#) [P 5160](#)