

# S25 RELAY

## SHORI

### ◆ Features

- 20A/30A general purpose power relay
- SPDT,DPDT and TPDT contact configurations
- DC and AC coil
- Socket and PCB terminal available

### ◆ Coil Data (DC)

Rated voltage (V)	Coil Resistance ±10% at 25 °C (Ω)	Rated Current ±10% (mA)	Pick up Voltage (Max)	Drop out Voltage (Min)	Max continuous Voltage	Power consumption At rated Voltage
SP DP	6	32	80% of rated voltage	10% of rated voltage	130% Max of Rated voltage	Approx. 1.2W
	12	120				
	24	472				
	48	1800				
	110	10000				
	125	10000				
TP	6	21.3	80% of rated voltage	10% of rated voltage	130% Max of Rated voltage	Approx. 1.7W
	12	85				
	24	340				
	48	1360				
	110	8500				
	125	8500				

# S25 RELAY

**SHORI**

## ◆ Coil Data (AC)

Rated voltage (V)	Coil Resistance $\pm 10\%$ at 25 °C ( $\Omega$ )	Pick up Voltage (Max)	Drop out Voltage (Min)	Max continuous Voltage	Power consumption At rated Voltage	
SP DP	6	4.2	85% of rated voltage	30% of rated voltage	110% Max of Rated voltage	Approx.3.0VA
	12	18				
	24	72				
	110	1580				
	120	1700				
	220	5850				
	240	7200				
TP	6	3.9	85% of rated voltage	30% of rated voltage	110% Max of Rated voltage	Approx.3.4VA
	12	14.5				
	24	64				
	110	1450				
	120	1540				
	220	5850				
	240	6750				

## ◆ Contact Rating

Resistive load	30A/250VAC, 20A/28VDC
----------------	-----------------------

# S25 RELAY

## SHORI

---

### ◆ Ordering information

S25 - 12VDC -2C S- F  
1            2            3    4    5

1. S25 -- Basic series designation
2. 12VDC--CoilVoltage
3. 1A --Single pole normally open  
1B --Single pole normally closed  
1C --Single pole double throw  
2A --Double pole normally open  
2B --Double pole normally closed  
2C --Double pole double throw  
3A --Three pole normally open  
3B --Three pole normally closed  
3C --Three pole double throw
4. S --Quick connect terminals  
P --PCB terminals
5. Blank --Standard type  
F --Class F

# S25 RELAY


SHORI

## ◆ Specification


Contact material	Ag Alloy	
Contact resistance	100 mΩ Max	
Operate time	25 ms Max	
Release time	20 ms Max	
Insulation resistance	100 MΩ Min. (DC 500V)	
Dielectric strength	Between open contact : AC1500V ,50/60Hz 1 min.	
	Between contact and coil : AC 3000V, 50/60Hz 1 min.	
	Between contact circuits : AC 3000V, 50/60Hz 1 min	
Vibration resistance	Operating extremes	10~50Hz, amplitude 1.5 mm
	Damage limits	10~50Hz, amplitude 1.5 mm
Shock resistance	Operating extremes	10G
	Damage limits	100G
Life expectancy	Mechanical	10,000,000 operations (frequency 18,000 operations/hr)
	Electrical	100,000 operations (frequency 360 operations/hr)
Operating ambient temperature	-30~+55°C (no freezing)	
Weight	Approx 80 g	

## ◆ Outline Dimension

S25(S)



S25(P)



# S25 RELAY


SHORI

---


## ◆ Wiring Diagram

BOTTOM VIEW


1C




2C




3C




1B




2B




3B



1A



2A



3A

