

SILVYN® SI

SILVYN® SI - grey soft PVC conduit



Low weight



Flame-retardant

Benefits

- Protection against dust
- Protection against humidity
- Low abrasion protection

Application range

- Easy cable protection
- Additional insulation
- Bundling and guiding of cables and wires

Product features

- Flexible
- Soft

Product Make-up

Soft-PVC conduit

SILVYN® SI**Technical Data**

Classification ETIM 5:	ETIM 5.0 Class-ID: EC001177 ETIM 5.0 Class-Description: Protective plastic hose
Classification ETIM 6:	ETIM 6.0 Class-ID: EC001177 ETIM 6.0 Class-Description: Protective plastic hose
Note:	Flame-retardant and self-extinguishing Dielectric strength: 25 kV/mm Tear-resistance: 23 N/mm ² Shore A hardness: 75 °C to 90 °C
Colour delivered:	Silver grey (RAL 7001)
Material:	Soft PVC
Temperature range:	-5°C to +80°C

Note

Photographs and graphics are not to scale and do not represent detailed images of the respective products.
Prices are net prices without VAT and surcharges. Sale to business customers only.

**SILVYN® SI**

Article number	ID x OD mm	Suitable for SILVYN® SSV- M/SSVZ-M	Suitable for SILVYN® SSV/SSVZ	Suitable for SILVYN® SCH
SILVYN® SI				
61713210	7.0 x 9.0	12/1 / -	-	10 - 16 S
61713240	9.0 x 12.0	12/2 / -	-	10 - 16 S
61713270	11.0 x 14.0	16/1 / -	-	10 - 16 S
61713300	13.0 x 16.0	16/2 / -	-	12 - 20 S
61713330	14.0 x 18.0	20/1	-	12 - 20 S
61713360	18.0 x 22.0	20/3	13,5/1	16 - 25 S
61713390	23.0 x 28.0	25	21	25 - 40 S
61713420	32.0 x 38.0	32 / 32/2	29/2	32 - 50 S

Last Update (09.04.2018)

©2018 Lapp Group - Technical changes reserved

Product Management www.lappkabel.de

You can find the current technical data in the corresponding data sheet.

PN 0456 / 02_03.16