

## SL510 Sound Level Meter



Extech's ultra-compact sound meter meets class 2 standards with ±1dB high accuracy that allows for quick and reliable sound level testing. It features a large backlit display for easy viewing and measures A & C weighting from 35 to 130dB with Fast and Slow response time mode. Size is small enough to conveniently fit in your pocket and includes a wrist strap.

Applications:

- Sound check
- Building Insulation
- Concerts

- Neighborhood disturbances
- Restaurants/nightclubs
- Workplace noise
- Airports



## **Features**

- ±1dB high accuracy meets Class 2 standards (IEC 61672-2013 and ANSI/ASA S1.4/Part 1
- Backlit LCD to view in dimly lit areas
- Data Hold and Min/Max functions
- Auto power off with disable

- Tripod mount (optional TR100 Tripod sold separately)
- Complete with microphone wind-screen, wrist strap, and three AAA batteries

Specifications	Range
Range	35 to 130dB
Basic Accuracy	±1dB @ 1KHz
Resolution	0.1dB
Weighting	A & C
Response Time	Fast/Slow
Microphone	Electret condenser 0.5" (12.7mm)
Dimensions	6.6x1.8x1.2" (167x45x20mm)
Weight	5.6oz (160g)

## **Ordering**

SL510 ..... Sound Level Meter

2 ) ) October 703050475103

UPC Code: 793950475102

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Environmental Test Equipment category:

Click to view products by Extech manufacturer:

Other Similar products are found below:

CW40 F150C10E3DRT F150LTC20 F150CD10E2 F150L75 F150LRS S-11 FLUKE-LDG 382153 FM100 RH210 382253 MO290-P

GEO-CABLE-REEL-50M T197914 RD300-L IR11BD IR11GM IR12GM IR21BD IR31CE IR32BC IR33BC MP7217TC NGM-1 SGX
7NH3 UT381 F150-SLC50 AW-CO-1000 AW-NmHc-100 3.000.401 AX-7535 CS-9S6SS-A P 2800 A P 2801 P 2802 P 5039 P 5130 P

5055 P 5060 P 5065 P 5086 P 5090 P 5110 P 5115 P 5135 P 5140 P 5145 P 5150 P 5160