

Common Mode Filters

For ultra high-speed differential signal line (HDMI, DVI, DisplayPort, USB3.0, etc.)

ACM series

Type: ACM2012D [0805 inch]*

ACM2012H [0805 inch]

* Dimensions Code [EIA]

Issue date: September 2011

[•] All specifications are subject to change without notice.

[•] Conformity to RoHS Directive: This means that, in conformity with EU Directive 2002/95/EC, lead, cadmium, mercury, hexavalent chromium, and specific bromine-based flame retardants, PBB and PBDE, have not been used, except for exempted applications.

&TDK

Common Mode Filters For Ultra High-speed Differential Signal Line (HDMI, DVI, DisplayPort, USB3.0, etc.)

Conformity to RoHS Directive

ACM Series ACM2012D/H

FEATURES

- These are a series of broadband common mode filters developed for high-speed differential signal interfaces, such as DVI and HDMI™.
- The cutoff frequencies in differential mode for ACM2012D and ACM2012H are 3.5GHz and 6.0GHz respectively, so they do not interfere with high-speed differential signals.
- The characteristic impedance is approximated to 100Ω, conforming to the TDR standard for HDMI™.

APPLICATIONS

- For new HDMITM interfaces used in digital video devices:
 ACM2012H is suited for use on the transmission side (Source)
 of digital TVs, DVD recorders and liquid crystal projectors.
 ACM2012D is suited for use on the receiving side (Sink).
- For digital video signal interfaces DVI (UXGA) used in PCs and other devices/High-speed differential signal interfaces for USB 2.0, IEEE1394 and Serial ATA.

TEMPERATURE RANGES

Operating	−25 to +85°C	
Storage(After mount)	−25 to +85°C	

PACKAGING STYLE AND QUANTITIES


Packaging style	Reel	Quantity		
Tanina	ø180mm	2000 pieces/reel		
Taping	ø330mm	10000 pieces/reel		

PRODUCT IDENTIFICATION


ACM	2012	D -	900	- 2P	- T	
(1)	(2)	(3)	(4)	(5)	(6)	(7)

- (1) Series name
- (2) Dimensions L×W 2012: 2.0×1.2mm
- (3) Product identification number (D or H)
- (4) Impedance[at 100MHz] 900: 90Ω
- (5) Number of line 2P: 2-line
- (6) Packaging styleT: ø180mm reel tapingTL: ø330mm reel tapingB: Bulk
- (7) TDK internal code

RECOMMENDED SOLDERING CONDITIONS RECOMMENDED TEMPERATURE PROFILE FOR LEAD-FREE SOLDER




REFLOW PROFILE FOR SOLDER HEAT RESISTANCE




- HDMI™ is trademark of HDMI Licensing, LLC.
- Conformity to RoHS Directive: This means that, in conformity with EU Directive 2002/95/EC, lead, cadmium, mercury, hexavalent chromium, and specific bromine-based flame retardants, PBB and PBDE, have not been used, except for exempted applications.

ATDK


SHAPES AND DIMENSIONS/CIRCUIT DIAGRAM



RECOMMENDED PC BOARD PATTERN ACM2012D TYPE



ACM2012H TYPE




ELECTRICAL CHARACTERISTICS


Part No.	Impedar (Ω) at 100M min.		DC resistance(Ω)max. [1 line]	Rated current Idc (mA)max.	Rated voltage Edc (V)max.	Insulation resistance $(M\Omega)$ min.	Cutoff frequency (GHz)typ.	Characteristic impedance (Ω) typ.
ACM2012D-900-2P	65	90	0.30	300	20	10	3.5	100
ACM2012H-900-2P	65	90	0.30	300	20	10	6	100

TYPICAL ELECTRICAL CHARACTERISTICS IMPEDANCE vs. FREQUENCY CHARACTERISTICS(REFERENCE)


ACM2012D-900-2P




ACM2012H-900-2P



INSERTION LOSS vs. FREQUENCY CHARACTERISTICS (REFERENCE)



CHARACTERISTIC IMPEDANCE MEASURED ACCORDING TO TDR(REFERENCE)



[•] All specifications are subject to change without notice.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for EMI Filter Circuits category:

Click to view products by TDK manufacturer:

Other Similar products are found below:

EMI2180MTTBG EMI8041BMUTAG CM1442-08CP CSPEMI204FCTAG SBSPP1000152MXT SBSGC5000473MXT

SBSMC0500474MXT EMI8043MUTAG 1-6609037-5 BNX022-01L BNX024H01L NZF220DFT1G MEM2012SC151T001

MEA2010PE150T001 MEA1608PE220TA0G MEA1608LC150T001 742730023 MEM2012F101R NFA21SL287V1A45L

MEM1608P101RT001 SBSMP1000224MXT SBSMC5000683MXT SBSMC0500474MXB SBSGP1000104MXB SBSGP1000104MXT

SBSGC5000102MXB MEM2012V301R MEM1608P75R0T001 NFA18SD187X1A45L VEMI355A-HAF-G-08 4420P-601-250/181

EMI220T-RC EMI221T-RC EMI271T-RC EMI470T-RC EMI101T-RC EMI222T-RC SBSMP0500474MXB SBSGC0500224MXT

BNP002-02 BNP002-03 BNX002-11 BNX003-11 BNX005-11 BNX012-01 NFA18SL407V1A45L NFA21SL317V1A45L

NFW31SP206X1E4L NFW31SP506X1E4L IP4254CZ16-8-TTL,1