

SP505 Pocket Solar Power Light Meter



Extech's SP505 measures solar power level from outdoor sunlight to determine the best location of solar panel and solar water heater installations. It is also used indoors by window manufacturers, automotive industry, and remodeling home owners to check the level of solar radiation transmission through various glass thicknesses and degrees of tinting to use for window installations. Convenient pocket-sized meter with built-in precision solar light sensor is easy-to-use wherever you go.



Features

- Measure solar power light level in watts per square meter (W/m²) or BTU (ft²*h)
- Built-in solar light sensor with precision photo diode
- Zero function
- Data Hold freezes current reading on display
- Tripod mount (optional TR100 Tripod sold separately)
- · Complete with two AAA batteries and a pouch

Specifications	Range	Max Resolution	Basic Accuracy
Measuring Ranges	3999 W/m²	1 W/m ²	±10 W/m²
	634 BTU/(ft ^{2*} h)	1 BTU/(ft ² *h)	±3 BTU (ft²*h) or ±5% whichever is greater
Spectral Response	400 nm to 1100 nm		
Dimensions	4.3 x 1.9 x 1" (108 x 48 x 23mm)		
Weight	2.8oz (80g)		

Ordering

SP505	Pocket Solar Po	wer Light Meter
TR100	Tripod	

UPC Code: 793950485057

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Environmental Test Equipment category:

Click to view products by Extech manufacturer:

Other Similar products are found below:

CW40 F150C10E3DRT F150LTC20 F150CD10E2 F150L75 F150LRS S-11 FLUKE-LDG 382153 FM100 RH210 382253 MO290-P

GEO-CABLE-REEL-50M T197914 RD300-L IR11BD IR11GM IR12GM IR21BD IR31CE IR32BC IR33BC MP7217TC NGM-1 SGX
7NH3 UT381 F150-SLC50 AW-CO-1000 AW-NmHc-100 3.000.401 AX-7535 CS-9S6SS-A P 2800 A P 2801 P 2802 P 5039 P 5130 P

5055 P 5060 P 5065 P 5086 P 5090 P 5110 P 5115 P 5135 P 5140 P 5145 P 5150 P 5160