



# TBA

## Braided sleeving in basalt fibre untreated, non-impregnated



### Standards\*

- Compliant with directive RoHS 2011/65/EU
- NF EN 60684-1 (10-2003)
- NF EN 60684-2 (07-2012)

### Colours and packagings

- Manufactured diameters : from 2 to 50 mm
- Standard colour : Khaki (natural)
- Standard packaging : Bobbins

### Chemical composition

- SiO<sub>2</sub>, Al<sub>2</sub>O<sub>3</sub>, MgO, CaO, FeO, Fe<sub>2</sub>O<sub>3</sub>, Fe<sub>2</sub>O<sub>3</sub>
- Asbestos free and halogen free guaranteed

### Characteristics

- Continuous working temperature : from -260°C to +560°C.  
Peaks at +600°C
- Fireproof
- Resistance to flame : non flammable
- Low heat expansion coefficient
- Good flexibility
- Very high chemical resistance, especially to acid
- Good mechanical resistance
- Low rate of moisture absorption
- Good thermal insulation properties
- Low density
- Good behaviour with soldering iron : no retraction
- Frays slightly when cut
- 100% recyclable

### Applications



\*Our products pass all or parts of requirements for the above-mentioned standards. The technical information written on our datasheets correspond to the most recent knowledges we have on those products, but the user is not exempted to verify the performances in the real particular context of application.

