



Heat Shrinkable Tubing 3:1 flexible and transparent

TF34

Protects wire and cable markers subject to abuse, while permitting inspectability of each item covered. Protects electronic components while permitting their identification and inspection.

Features and Benefits

- Transparent, flexible polyolefin tubing
- Protects identification marking perfect
- Few sizes cover a wide range of diameters allowing reduced inventory
- Halogen free



TF34 transparent tubing with 3:1 shrink ratio allowing for a wider range of application.



Detailed Information about Heatguns please refer to page 529.



One Step to the Web!

| | |
|--|---------------------------------|
| MATERIAL | Polyolefin, cross-linked (PO-X) |
| Shrink Ratio | 3:1 |
| Operating Temperature | -55 °C to +135 °C |
| Minimum Shrink Temperature | +110 °C |
| Longitudinal change after shrinkage | -5 % max. |
| Dielectric Strength | 46 kV/mm |
| Flammability | not flame retarded |



Heat Shrinkable Tubing 3:1

| TYPE | Supplied Ø D min. | Recov. Ø d max. | Wall (WT) | Reel Length | Colour | Article-No. |
|--------------|-------------------|-----------------|-----------|-------------|------------------|-------------|
| TF34-1.5/0.5 | 1.5 | 0.5 | 0.50 | 30 m | Transparent (CL) | 333-30153 |
| TF34-3/1 | 3.0 | 1.0 | 0.50 | 30 m | Transparent (CL) | 333-30303 |
| TF34-6/2 | 6.0 | 2.0 | 0.70 | 30 m | Transparent (CL) | 333-30603 |
| TF34-9/3 | 9.0 | 3.0 | 0.80 | 30 m | Transparent (CL) | 333-30903 |
| TF34-12/4 | 12.0 | 4.0 | 0.85 | 30 m | Transparent (CL) | 333-31203 |
| TF34-18/6 | 18.0 | 6.0 | 1.00 | 30 m | Transparent (CL) | 333-31803 |
| TF34-24/8 | 24.0 | 8.0 | 1.20 | 30 m | Transparent (CL) | 333-32403 |
| TF34-40/13 | 40.0 | 13.0 | 1.25 | 30 m | Transparent (CL) | 333-34003 |

All dimensions in mm. Subject to technical changes.
Minimum Order Quantity (MOQ) may differ from package content.