

Datasheet for part number DCMM-8W8SA197

Our Catalog Part Number: DCMM-8W8S-A197

Brand: Cannon Product Category: D Sub Product Line: D Sub Series: COMBO D

Product Datasheet	
General	Combo D Series: D-Subminiature offering mixed layouts
Wire Gauge Range AWG	AWG 8-26
Mating Cycles	500
Contact Arrangement	8W8 (8 empty size 8 cavities)
Dielectric Withstanding Voltage	500 VAC at sea level
Current Rating Signal Contacts	7.5 max
Contact Resistance	10 milli Ohm max
Operating Temperature	-55°/+150°
Salt Spray Test	48 hours {96 Hrs for Stainless Steel}
Shell Material	steel
Shell Finish	pure tin over nickel
Insulator Material	Thermoplastic, type PCT UL 94V-0
Insulator Color	black
Gender	Socket
Contact Type	Solder pot
Contact Material	copper alloy
Contact Finish	gold over nickel (Performance Class 1)
Mounting Method	.120" (3,05mm) Through Hole

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for itt manufacturer:

Other Similar products are found below:

BKAF3-68102-25 MS3106E22-14P MS3106E22-22PY MS3100E22-22P MS3106E22-22PX MDM-37PCBR-F222 CA3108E14S-5PBA176A232 KPSE06F20-41SA206F0 CB2-18-3SCA232 KPSE00F106PWF0 KPSE00F10-6P-FO CT6E18-11SCA206 CA3101E10SL-4SF80DN MS3100F14S-7S CA3101E10SL-4PBA176F42 MS3101E181SW KPSE00E10-6PW 024251-0016-R 024253-0025 024265-0001 024270-0015 024271-0022 024273-0043 024288-0001 M24308/23-57Z M24308/24-21F M24308/24-33Z CT1F22-7SS CT2-20-23SWS CT2-20-23SXS CT2-36-10PCAU CT6-24-11PSA206 CT6F36-10PCA152 CT6F9767-14-4-14S-5PC CT6T9767-14-4-14SA7SS D38999/20FG16PA-LC - MD1-21PS MDM-15PH001B-A174 MDM-15PH003B-A174 MDM-21SCBR-A174 MDM-21SCBRP-A174 MDM-21SCBRP-A174 MDM-21SCBRP-BR MDM-21SCBR MDM