




# MULTIPLE CONFIGURATION PCB HEADERS & RECEPTACLES



Active

PRODUCT DRAWING  
English

3D PDF

TE CONNECTIVITY (TE)

## 24 MODII HDR DRST B/A .100CL

AMPMODU | AMPMODU Headers

1-103186-2

TE Internal Number: 1-103186-2

Not EU RoHS or ELV Compliant

[Find Compliant Alternatives](#)

Applies To **Printed Circuit Board**

Connector Style **Plug**

Centerline **2.54 mm [ .1 in ]**

Number of Positions **24**

Header Type **Breakaway**

### Product Drawings

[HEADER ASSY, MOD II, BREAKAWAY, DOUBLE ROW, .100X.100 C, VERTICAL, WITH .025 SQ POSTS](#)

PDF  
English

### CAD Files

[Customer View Model](#)

2D\_DXF.ZIP  
English

[Customer View Model](#)

3D\_IGS.ZIP  
English

[Customer View Model](#)

3D\_STP.ZIP  
English

[3D PDF](#)

PDF  
English

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

### Product Type Features

Applies To

**Printed Circuit Board**

Connector Style

**Plug**

PCB Mounting Orientation

**Vertical**

Connector Type

**Header**

Row-to-Row Spacing

**2.54 mm [ .1 in ]**

Stabilizers

**Without**

Strain Relief

**Without**

	Strain Relief	<b>Without</b>
	Board Standoff	<b>Without</b>
	Product Type	<b>Connector</b>
	Gasket	<b>Without</b>
Configuration Features	Number of Positions	<b>24</b>
	Number of Rows	<b>2</b>
	Keyed	<b>No</b>
	Selectively Loaded	<b>No</b>
Electrical Characteristics	Dielectric Withstanding Voltage	<b>750 V</b>
Body Features	Header Type	<b>Breakaway</b>
	Post Size	<b>.64 mm [ .025 in ]</b>
Contact Features	Contact Protection	<b>Without</b>
	Contact Shape	<b>Square</b>
	Contact Type	<b>Pin</b>
	Contact Base Material	<b>Phosphor Bronze</b>
	Contact Mating Area Plating Thickness (µin)	<b>15</b>
	Solder Tail Contact Plating Material	<b>Tin-Lead over Nickel</b>
	Contact Mating Area Plating Material	<b>Gold</b>
	Contact Current Rating (A)	<b>3</b>
Termination Features	Termination Post Length	<b>3.05 mm [ .12 in ]</b>
	Termination Method to PC Board	<b>Through Hole</b>
Mechanical Attachment	PCB Mounting Style	<b>Through Hole</b>
	PCB Mount Retention	<b>Without</b>
	Panel Mount Retention	<b>Without</b>
	Mating Connector Lock	<b>Without</b>
Housing Features	Centerline	<b>2.54 mm [ .1 in ]</b>
	Housing Material	<b>Thermoplastic</b>
Dimensions	Mating Post Length	<b>5.84 mm [ .23 in ]</b>

Usage Conditions	Operating Temperature Range (°C)	<b>-65 – 105</b>
	High Temperature Housing	<b>No</b>
<hr/>		
Operation/Application	High Speed Serial Data Connector	<b>No</b>
<hr/>		
Industry Standards	UL Flammability Rating	<b>UL 94V-0</b>
	Approved Standards	<b>CSA LR7189, UL E28476</b>
<hr/>		
Packaging Features	Packaging Quantity	<b>120</b>
	Packaging Method	<b>Carton</b>
<hr/>		
Other	Comment	<b>Headers may be broken to desired number of positions using Hand Tool No. 91406-1, or Tool Kit No. 314818-1. Other tail lengths are available, consult TE Connectivity.</b>
<hr/>		
Product Compliance	<a href="#">Statement of Compliance</a> PDF	
	<a href="#">VIEW ALL PRODUCT COMPLIANCE</a>	

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Headers & Wire Housings](#) category:*

*Click to view products by [TE Connectivity](#) manufacturer:*

Other Similar products are found below :

[95000-104TRLF](#) [10135584-644402LF](#) [DF62W-EP2022PCA](#) [95000-106TRLF](#) [DF62W-2022SCA](#) [DF62W-EP2022PC](#) [2203348](#) [DF62W-2022SC](#) [1084018](#) [1029039](#) [1084017](#) [802-10-012-10-002000](#) [1112640](#) [1112639](#) [000-34000](#) [0009482033](#) [0009507031](#) [57102-S06-03LF](#) [57202-S52-04LF](#) [PCN6-15S-2.5E](#) [0039019024](#) [58102-G61-06LF](#) [582553-1](#) [0009485154](#) [0009508121](#) [0022285053](#) [0050291907](#) [018731A](#) [LY20-4P-DT1-P1E-BR](#) [02.125.8002.8](#) [60101931](#) [60598-1 \(Cut Strip\)](#) [M1625-3R/100](#) [61062-3](#) [61082-181009](#) [636-1427](#) [638009-1](#) [641938-9](#) [641991-4](#) [644168-1](#) [647662-1](#) [65039-019ELF](#) [65817-002LF](#) [65817-015LF](#) [65863-015LF](#) [66207-023LF](#) [67016-026LF](#) [67046-001LF](#) [67095-007LF](#) [67230-005LF](#)