

MULTIPLE CONFIGURATION PCB HEADERS & **RECEPTACLES**





✓ Active

PRODUCT DRAWING



♣ 3D PDF

TE CONNECTIVITY (TE)

08 MODII HDR SRST B/A .100CL

AMPMODU | AMPMODU Headers

103321-8

TE Internal Number: 103321-8

Not EU RoHS or ELV Compliant Find Compliant Alternatives

Applies To Printed Circuit Board

Connector Style Plug

Centerline 2.54 mm [.1 in]

Number of Positions 8

Header Type Breakaway

Product Drawings

ASSEMBLY, HEADER, BREAKAWAY, MOD II, SINGLE ROW, .100 C/L, VERTICAL,

WITH .025 SQUARE POSTS

PDF **English**

CAD Files

Customer View Model

2D_DXF.ZIP English

Customer View Model

3D_IGS.ZIP English

Customer View Model

3D_STP.ZIP English

3D PDF PDF English

Product Environmental Compliance

TE Material Declaration

MD_103321-8_11062015117_dmtec

PDF **English**

Please review product documents or contact us for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features

Applies To

Printed Circuit Board

Connector Style

Plug

PCB Mounting Orientation

Vertical

Cannastar T....

U ~ ~ d ~ ...

	Connector Type	neager
	Row-to-Row Spacing	2.54 mm [.1 in]
	Stabilizers	Without
	Strain Relief	Without
	Board Standoff	Without
	Product Type	Connector
	Gasket	Without
Configuration Features	Number of Positions	8
Configuration reactives	Number of Rows	
		1
	Keyed	No
	Selectively Loaded	No
Electrical Characteristics	Dielectric Withstanding Voltage	750 V
Body Features	Header Type	Breakaway
	Post Size	.64 mm [.025 in]
Contact Features	Contact Protection	Without
	Contact Shape	Square
	Contact Type	Pin
	Contact Base Material	Phosphor Bronze
	Contact Mating Area Plating Thickness (µin)	100 – 200
	Solder Tail Contact Plating Material	Tin-Lead over Nickel
	Contact Mating Area Plating Material	Tin-Lead
	Contact Current Rating (A)	3
Termination Features	Termination Post Length	3.18 mm [.125 in]
	Termination End Plating Thickness (µin)	100 – 200
	Termination End Plating Material	Tin-Lead Over Nickel
	Termination Method to PC Board	Through Hole
Mechanical Attachment	PCB Mounting Style	Through Hole
	PCB Mount Retention	Without
	Panel Mount Retention	Without
		Without
	Mating Connector Lock	viidiout

Housing Features Centerline 2.54 mm [.1 in] Housing Color Black Housing Material Thermoplastic Dimensions Mating Post Length 8.08 mm [.318 in] **Usage Conditions** Operating Temperature Range (°C) -65 – 105 High Temperature Housing No Operation/Application High Speed Serial Data Connector No **UL 94V-0** Industry Standards **UL Flammability Rating** Approved Standards CSA LR7189, UL E28476 200 Packaging Features Packaging Quantity Packaging Method Carton Other Comment Headers may be broken to desired number of positions using Hand Tool No. 91406-1, or Tool Kit No. 314818-1. Other tail lengths are available, consult TE Connectivity. **Product Compliance** Statement of Compliance VIEW ALL PRODUCT COMPLIANCE





Connectors - FFC Connectors FFC | FFC 008 HOUSING FFC RCPT 100CL SR - 487378-7 TE INTERNAL NUMBER: 487378-7 ✓ Active

Connector Type Housing Connector Style Receptacle Centerline 2.54 mm

Always EU RoHS/ELV Compliant

Number of Positions 8

Number of Rows 1

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Headers & Wire Housings category:

Click to view products by TE Connectivity manufacturer:

Other Similar products are found below:

95000-104TRLF 10135584-644402LF DF62W-EP2022PCA 95000-106TRLF DF62W-2022SCA DF62W-EP2022PC 2203348 DF62W-2022SC 1084018 1029039 1084017 802-10-012-10-002000 1112640 1112639 000-34000 0009482033 0009507031 57102-S06-03LF 57202-S52-04LF PCN6-15S-2.5E 0039019024 58102-G61-06LF 582553-1 0009485154 0009508121 0022285053 0050291907 018731A LY20-4P-DT1-P1E-BR 02.125.8002.8 60101931 60598-1 (Cut Strip) M1625-3R/100 61062-3 61082-181009 636-1427 638009-1 641938-9 641991-4 644168-1 647662-1 65039-019ELF 65817-002LF 65817-015LF 65863-015LF 66207-023LF 67016-026LF 67046-001LF 67095-007LF 67230-005LF