


RAY-90 Issue 3 17th April 2007 Page 1 of 2

Page 2 is for internal use only

## RAYBRAID® PLATED COPPER BRAID

The complete requirements for procuring the wire described herein shall consist of this document.



Part	Braid Detail				
Number	Strand	Number of		Minimum	Nom.
	size			Coverage	Weight #
	AWG/ mm	Carriers	Ends	%	(kg/ km)
RAY-90-3.0	36/ 0.13	16	5	90.0	13
RAY-90-4.0	36/ 0.13	16	7	90.0	17
RAY-90-5.0	36/ 0.13	24	6	90.0	21
RAY-90-6.0	36/ 0.13	24	7	90.0	25
RAY-90-10.0	34/ 0.16	24	9	90.0	52
RAY-90-12.5	34/ 0.16	24	10	90.0	65
RAY-90-15.0	32/ 0.20	24	11	90.0	100
RAY-90-20.0	30/ 0.25	36	7	90.0	165
RAY-90-25.0	30/ 0.25	36	9	90.0	207
RAY-90-30.0	28/ 0.32	36	9	90.0	310

NOTE:

The last number of the part depicts the nominal internal diameter of the braid, e.g. RAY-90-5.0 Tin Plated Copper Braid with 5.00 mm nominal internal diameter.

'#' The nominal weight value excludes weight of former

PERFORMANCE REQUIREMENTS:

To be tested to and meet the requirements of the issue in effect of WSD 1922.

APPROVAL:

Electronic sign off - no signatures will appear.

RAYBRAID<sup>®</sup> is a registered trademark of Tyco Electronics Corporation.

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Non-Heat Shrink Tubing and Sleeves category:

Click to view products by TE Connectivity manufacturer:

Other Similar products are found below:

601203-000 CTA-0053 8429-9 8445-7.5 8450 120-116-1-1-09BE 120-116-1-1-09BF 120-116-1-1-09BP 120-116-1-1-12BE 120-116-1-1-12BE 120-116-1-1-12BP 120-123-06 120-123-10 120-125-12BL 120-125-12R 120-125-20R 120-126-09 120-126-09BL 120-126-12 120-126-12BL 12