

Datasheet for part number DBMM-25S

Our Catalog Part Number: DBMM-25S

Our Global Manufacturing Part Number: 051523-0000

Brand: Cannon Product Category: D Sub Product Line: D Sub Series: D*M

| Product Datasheet | |
|---------------------------------|--|
| General | D*M High reliable D-Sub Connectors |
| Wire Gauge Range AWG | AWG 20-28 |
| Mating Cycles | 500 |
| Contact Arrangement | 25 contacts size 20 |
| Dielectric Withstanding Voltage | 1000 VAC at sea level |
| Current Rating | 7.5 A max |
| Contact Resistance | 7.5 milli Ohm max |
| Operating Temperature | -55°/+150° |
| Salt Spray Test | 48 hours {96 Hrs for Stainless Steel} |
| Shell Material | steel |
| Shell Finish | Yellow chromate over zinc |
| Insulator Material | Thermoplastic, type PCT UL 94V-0 |
| Insulator Color | black |
| Gender | Socket |
| Contact Type | Solder Pot |
| Contact Material | copper alloy |
| Contact Finish | gold over nickel (Performance Class 2) |
| Hardware | .120" (3,05mm) Through Hole |
| Disclaimer | Our facility is not currently certified by the DLA and this product is not covered by the QPL/QML. |

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for D-Sub MIL Spec Connectors category:

Click to view products by ITT manufacturer:

Other Similar products are found below:

M24308/4-13Z M8351307-B D38999/20FJ43HN D38999/24WG11PB-LC D38999/24WG41HN MDM-15PH041P MDM-21PH041P MDM-21SH003B-K139 850-056-0812 1218697-4 DBMM25S MS27467T21F41S 17D25HV 1996840-1 243082-15 1663962-1 1757682-1 17D-E51218-1 17SDA15S 1883533-1 1883886-1 1883889-1 192900-0377 308-CP6P0441-024H M24308/2-3Z M24308/4-3Z M24308/4-4F M24308/4-4Z M24308/8-347 M83513/03-E09C M83723/75W2212N L/C D38999/24FJ29PN-LC D38999/24WG11SB-LC MDM-21PH046P 5-1218949-1 550-031NF1R6K 550E001NF1R3J0L 550T001NF1R6K0L 557T283NF5B08 C115368-1612B C115370-1717B DC121073157 443869-3 443869-4 443869-5 550S004NF1R1B0F03 550-031NF1R2E 550E003M2R9J0F04 550E003M3R9J0F05 550E024M104R9J0