



Humidity/Temperature/Pressure Datalogger

Records Humidity, Temperature and Atmospheric Pressure

Datalogs up to 10,000 readings with a user programmable sample rate

Features:

- USB interface for easy set-up and data download
- · Selectable Atmospheric Pressure Units: psi, hPa, kPa, and bar
- Selectable data sampling rate from 1 minute to 18 hours
- · User-programmable Min/Max alarm thresholds
- Manual and Programmable start modes
- Status Indication via Red/Yellow LED and Green LED
- Long battery life
- Complete with 3.6V Lithium battery, mounting bracket, and Windows[®] 98, 2000, XP, and Vista compatible analysis software





Monitors Humidity, Temperature and Air Pressure levels in clean rooms, warehouses, storage rooms, freezers, shipping vans, and water damage restoration



USB connector easily plugs into a computer for data analysis

Specifications	Range	Resolution	Accuracy (%rdg+digits)
Temperature	-40 to 158°F	0.1°F/°C	±1.8°F (14 to 104°F)
			$\pm 3.6^{\circ}$ F (-40 to +14 and 104 to 158°F)
	-40 to 70°C		±1.0°C (-10 to 40°C)
			±2.0°C (-40 to -10 and +40 to 70°C)
Humidity	0 to 100%RH	0.1%RH	±3.5%RH
Air Pressure	13.7 to 15.2psi	0.1psi	
	950 to 1050hPa	0.1hPa	
	95 to 105kPa	0.1kPa	
	0.9 to 1.0bar	0.1bar	
Datalogging interval	1 minute to 18 hours		
Memory	10,000 points		
Dimensions	5.1 x 1.1 x 0.98" (130 x 30 x 25mm)		
Weight	1oz (20g)		

Ordering Information:

()

www.extech.com

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Environmental Test Equipment category:

Click to view products by Extech manufacturer:

Other Similar products are found below :

 CW40
 F150C10E3DRT
 F150LTC20
 F150CD10E2
 F150L75
 F150LRS
 S-11
 FLUKE-LDG
 382153
 FM100
 RH210
 382253
 MO290-P

 GEO-CABLE-REEL-50M
 T197914
 RD300-L
 IR11BD
 IR11GM
 IR21BD
 IR31CE
 IR32BC
 IR33BC
 MP7217TC
 NGM-1
 SGX

 7NH3
 UT381
 F150-SLC50
 AW-CO-1000
 AW-NmHc-100
 3.000.401
 AX-7535
 CS-9S6SS-A
 P 2800 A
 P 2801
 P 2802
 P 5039
 P 5130
 P

 5055
 P 5060
 P 5065
 P 5086
 P 5090
 P 5115
 P 5135
 P 5140
 P 5145
 P 5150
 P 5160