RJSSE Product Specification S6035C Rev 1.2

Amphenol

Now you're connected!



Overview

This product specification defines the general use and performance parameters for Amphenol's RJSSE Surface Mount series of inverted modular jacks.

Availability: Single and multiport connectors, shielded and unshielded versions available with or without light pipe option.

Usage

The RJSSE Surface Mount modular jacks supports Ethernet Protocols. Shielding available for increased EMI performance and Light Pipes for Link Activity and Network Speed verification.

Applications

Intended for use in applications such as: Networking & Telecom

- Wireless (WiMAX)
- Network servers

Hubs, routers, switches

Office & Home Equipment

- PC's, Laptops, Copiers/Printers
- Telephones, modems
- Surge Protectors
- ATMs, Vending Machines

Consumer Goods

- Security Systems
- Set Top Boxes
- Video Game Systems Miscellaneous
 - Multi-Media Equipment
 - Industrial Equipment
 - POS Terminals

P/N RJSAE-5385-02 SHOWN

STACKED 2x1, 8 POSITION, WITH SHIELD AND LEDS

P/N RJHSE-3081 SHOWN

SINGLE PORT VERTICAL MOUNT, NO SHIELD, WITH LEDs

P/N RJHSE-5385-02 SHOWN

TWO PORT REGULAR MOUNT, WITH SHIELD AND LEDS

RJSAE

Revision date: June 09, 2011

Amphenol

Page 1 of 2

Now you're connected!

About Amphenol

Commercial Products Amphenol's commercial connector products are used in a variety of end user applications including networking, telecom, server & computer, storage & HDD, consumer electronics and entertainment. professional audio & Industrial & Military/Aerospace.

Related Products

RJULE




P/N RJULE-4X182-01 SHOWN SINGLE PORT REGULAR MOUNT, STANDARD SHIFLD WITH SMT

FRJAE



P/N FRJAE-418 SHOWN SINGLE PORT, 8 POSITION, WITH FERRITE FILTER AND SHIELD (FRONT TABS)

RJLSE



P/N RJLSE-41181-01 SHOWN SINGLE PORT REGULAR MOUNT. STANDARD SHIFLD WITH SMT

Electrical Characteristics

Contact resistance: Insulation resistance: Current rating: Voltage rating: DWV

 $20 \text{ m}\Omega \text{ max}.$ 500 M Ω minimum at 500V DC for 2 minutes max. 1.5 Amps 125 Volts AC 1500 VAC, 60 Hz. 1 min.

Mechanical Characteristics

Mating connector insertion force: 5.0 lbs. Maximum. Mating connector pull retention force: 20 lbs Minimum. Durability: 750 mating & unmating cycles Suitable for IR Reflow (Light Pipes to be installed after soldering)

Operating temperature: -55° C to +85° C

Material Requirements

RJSSE connectors are RoHS compliant. Unless otherwise specified, the materials for each component shall be:

Insulator:

High Temp thermoplastic. Complies with UL 94V-0, Black color

Contacts:

- Phosphor Bronze hard temper with gold thickness options (6μ ", 15μ ", 30μ ", 50μ ") over 50µ" minimum Nickel on contact mating area.
- 100µ" minimum matte tin over nickel on soldering tail

Shield:

Copper alloy; Nickel or Matte Tin plating

- Light Pipe:
 - Optical grade polycarbonate, UL 94V-0

Available Documents

Drawing Numbers:

P-RJSSE-508X-XX P-RJSSE-5381-04 P-RJSSE-7061

Surface Mount, 8 Position Modular Jack, Unshielded, optional Light Pipes 4 Port, Surface Mount, 8 Position Modular Jack, Shielded with Light Pipes Surface Mount, 6 Position, Unshielded with Light Pipes Contact factory or Authorized Amphenol representative for additional configurations



Page 2 of 2

Copyright © Amphenol Corporation 2011 • All rights reserved



www.amphenolcanada.com

THIS DOCUMENT CONTAINS PROPRIETARY INFORMATION AND SUCH INFORMATION MAY NOT BE DISCLOSED TO OTHERS FOR ANY PURPOSE OR USED FOR MANUFACTURING PURPOSES WITHOUT WRITTEN PERMISSION FROM AMPHENOL CANADA CORP

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Modular Connectors / Ethernet Connectors category:

Click to view products by Amphenol manufacturer:

Other Similar products are found below :

 RJE231881317T
 MP1010RX-1000
 MP44RX-1000
 GAX-3-66
 GAX-8-62
 93606-0253
 GD-A-44
 GDCX-PA-66-50
 GDCX-PN-64
 GDCX-PN-64

 PN-66
 GDCX-PN-66-50
 GDLX-A-66
 GDLX-A-88
 GDLX-N-66
 GDLX-S-88K
 GDTX-S-88-50
 GDX-PA-1010
 GLX-N-1010M-BLK

 GLX-N-44M
 GLX-S-88M-BLK
 GMX-N-1010
 GMX-S-1010
 GMX-S-66
 GMX-SMT2-N-1010
 GMX-SMT2-N-64-50
 GMX-SMT2-S6-88

 GMX-SMT4-N-88
 GPX-2-64
 GRT1-BT1-5
 GSGX-N-2-88
 GSX-NS2-88-3.05
 GSX-NS2-88-3.05-50
 GSX-NS-88-3.05-30
 GSX-NS-88-3.05-30

 3.05-50
 GSX-NS-88-3.68
 1-1775629-2
 GWLX-S-88-GR
 GWLX-S9-88-YG
 1300500326
 1300500227
 1300530003
 1300570002
 1324640-4

 RJ11FTVC2G
 RJ11FTVC2N
 RJFTVX2SA1G
 132764-001
 1400000
 1413235
 MP88X-1000