## **Detailed Specifications & Technical Data**

METRIC MEASUREMENT VERSION



8920 Hook-up/Lead - UL AWM Style 1015

For more Information please call

1-800-Belden1



# General Description:

Tinned copper conductor, PVC insulation. Rated 105°C, 600V. Rated 2500V peak for electronic circuits, and internal wiring for electronic and electrical equipment.

#### Physical Characteristics (Overall) Conductor AWG: # Conductors AWG Stranding Conductor Material TC - Tinned Copper 7x30 Total Number of Conductors: Insulation Insulation Material: Insulation Material PVC - Polyvinyl Chloride 0.762 Overall Insulation Overall Cable Overall Nominal Diameter: 2.362 mm Mechanical Characteristics (Overall) Bulk Cable Weight: 8.632 Kg/Km Applicable Specifications and Agency Compliance (Overall) Applicable Standards & Environmental Programs UL Rating: 600 V, 105°C UL Type: MTW or AWM 1015/1230 CSA Rating: 600 V 105°C CSA Type: AWM I A/B or TEW EU Directive 2011/65/EU (ROHS II): Yes EU CE Mark: EU Directive 2000/53/EC (ELV): Yes EU Directive 2002/95/EC (RoHS): Yes EU RoHS Compliance Date (mm/dd/yyyy): 07/01/2005 EU Directive 2002/96/EC (WEEE): Yes EU Directive 2003/11/EC (BFR): Yes CA Prop 65 (CJ for Wire & Cable): Yes MII Order #39 (China RoHS): Flame Test UL Flame Test: VW-1 CSA Flame Test: FT1 Plenum/Non-Plenum Plenum (Y/N): No

## Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
8920 0011000	1,000 FT	7.000 LB	BROWN	Р	22 STR PVC BRN
8920 002100	100 FT	0.700 LB	RED		22 STR PVC RED
8920 0021000	1,000 FT	7.000 LB	RED	P	22 STR PVC RED
8920 0025000	5,000 FT	35.000 LB	RED		22 STR PVC RED

Page 1 of 2 08-26-2016

## **Detailed Specifications & Technical Data**

### METRIC MEASUREMENT VERSION



## 8920 Hook-up/Lead - UL AWM Style 1015

8920 0031000	1,000 FT	7.000 LB	ORANGE	Р	22 STR PVC ORG
8920 004100	100 FT	0.700 LB	YELLOW		22 STR PVC YEL
8920 0041000	1,000 FT	7.000 LB	YELLOW	Р	22 STR PVC YEL
8920 0051000	1,000 FT	7.000 LB	GREEN, DARK	Р	22 STR PVC GRN
8920 0071000	1,000 FT	7.000 LB	VIOLET	Р	#22 STR PVC VIO
8920 0081000	1,000 FT	7.000 LB	GRAY	Р	#22 STR PVC GRY
8920 009100	100 FT	0.700 LB	WHITE		22 STR PVC WHITE
8920 0091000	1,000 FT	7.000 LB	WHITE	Р	22 STR PVC WHITE
8920 010100	100 FT	0.700 LB	BLACK		22 STR PVC BLK
8920 0101000	1,000 FT	7.000 LB	BLACK	Р	22 STR PVC BLK
8920 0105000	5,000 FT	35.000 LB	BLACK	С	#22 STR PVC BLK
8920 013100	100 FT	0.700 LB	BLUE, DARK		22 STR PVC D BLU
8920 0131000	1,000 FT	7.000 LB	BLUE, DARK	Р	22 STR PVC D BLU

Notes:
C = CRATE REEL PUT-UP.
P = STRIPE COLORS ON STOCK SOLID COLORS. STRIPING ADDER OF \$8.00/M' FOR1 OR 2 STRIPES. 10000' MINIMUM ORDER FOR COLOR COMBINATION.PUT-UP WILL BE SUBJECT TO TWO PIECES (+ OR -) 10% PER SPOOL

Revision Number: 1 Revision Date: 08-26-2008

© 2016 Belden, Inc All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

product.
Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 2014/35/EU).

# **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Hook-up Wire category:

Click to view products by Belden manufacturer:

Other Similar products are found below:

002333-000 M81044/12-22-6 M81044/9-8-9 743094-001 81044/12-18-9CS3209 8538-009-1000 ATFC0311-20-5D EF5675-000 BFWUL3239-24-PINK 22759/34-16-9CS2621 933205-000 284711-000 961473-000 30802-009-250 30808-010-500 30810-010-500 99M0111-20-2 22759/43-10-9CS2873 265925-000 CM9524-000 CMC-0553-1-9 31510-010-250 31514-009-500 32412-009-500 34401-010-250 M81044/9-4-9 391441-BK007 400R0111-10-9 431660-000 ATFC0311-20-0 ATFC0311-20-3 44/7024-26-9-9 44A0112-22-9CS3184 456157-000 BFW-UL3239-24-WHITE 55/0312-26-6L-CS2570 55A0811-12-9 55A6087-20-9-9-9 55A6315-22-9-9CS2632 55A7400-22-9/96-9CS2275 55A9002-30-5 55PC0811-6-9CS2637 55PC1211-22-9-9CS3278 32820-009-5000 34020-008-2000 358838-000 391850-BK199 392075-RD199 W28-6HU 437545-000