

Digital Psychrometer

External Probe Temperature measurements for differential

Calculates T1-T2 differential (Air Temperature minus External Probe Temperature)

Features:

- Simultaneous display of %RH, Temperature and Dew point or Wet Bulb or Probe Temperature
- · Wet bulb measurements without slinging
- Calculates T1-T2 differential (Air Temperature minus External Probe Temperature) using optional probe (TP890) and T2-Dew Point
- Unique sensor cap design twists to closed position for protection during storage
- Switchable °F/°C temperature units with 0.1° resolution
- Data Hold freezes current reading on display
- Max/Min readings
- Auto power off to save battery life
- RH300 complete with 2 AAA batteries
- Optional external temperature probe (TP890)
- Optional kit RH305 includes RH300, temperature probe, 33% and 75% calibration bottles, and carrying case



RH300-CAL Optional calibration salt bottles



includes RH300, 33% and 75% calibration bottles, temperature probe, and carrying case.



Unique sensor cap design Twist to open or close sensor for storage.

Ordering Information:

RH300	Digital Psychrometer
RH300-	NISTRH300 with Calibration Traceable to NIST
RH305	Digital Psychrometer Kit
RH305-	NISTRH305 with Calibration Traceable to NIST
RH300-	CAL33% and 75% RH calibration reference
TP890	Optional Thermistor Temperature Probe (for Model RH300)



Specifications:	Range	Max Resolution	Basic Accuracy
Humidity	10 to 90%RH	0.1%RH	±3%RH
Temperature (internal)	-4 to 122°F (-20 to 50°C)	0.1°	$\pm 1.8^{\circ}$ F or $\pm 1^{\circ}$ C
Temperature (external)	-4 to 158°F (-20 to 70°C)	0.1°	$\pm 1.8^{\circ}$ F or $\pm 1^{\circ}$ C
Dew Point	-90.4 to 122°F (-68.0 to 49.9°	C)	
Wet Bulb	-6.9 to 122°F (-21.6 to 49.9°C)	
Dimensions 7 x 1.9 x 1" (178.5 x 48.4 x 24.7mm)			
Weight	3.3oz (95g)		

CE

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Environmental Test Equipment category:

Click to view products by Extech manufacturer:

Other Similar products are found below :

 CW40
 F150C10E3DRT
 F150LTC20
 F150CD10E2
 F150L75
 F150LRS
 S-11
 FLUKE-LDG
 382153
 FM100
 RH210
 382253
 MO290-P

 GEO-CABLE-REEL-50M
 T197914
 RD300-L
 IR11BD
 IR11GM
 IR21BD
 IR31CE
 IR32BC
 IR33BC
 MP7217TC
 NGM-1
 SGX

 7NH3
 UT381
 F150-SLC50
 AW-CO-1000
 AW-NmHc-100
 3.000.401
 AX-7535
 CS-9S6SS-A
 P 2800 A
 P 2801
 P 2802
 P 5039
 P 5130
 P

 5055
 P 5060
 P 5065
 P 5086
 P 5090
 P 5115
 P 5135
 P 5140
 P 5145
 P 5150
 P 5160