

Smart Technology. Delivered.

# Mini Directional Antenna



### MINI DIRECTIONAL ANTENNA, 2400 TO 2483 MHz OPERATION

The 2.4 GHz mini directional antennas offered by Laird are a sub-compact antenna for the most demanding client applications. The antennas offer high gain in an ultra-small, aesthetically pleasing package. These are constructed of gray color UV ABS plastic with aluminum backplate and a stainless steel mounting bracket.

The antenna can be used in horizontal or vertical polarization by making a change to the bracket mounting. The stainless steel bracket affords +/- 15° tilt adjustment. The compact, low visual impact attractive styling blends well in almost any application. The antenna comes with an integral N female connector standard.

### **FEATURES AND BENEFITS**

- 12 dBi gain in a mini directional antenna
- Rugged and weatherproof
- Ultra low wind loading and ultra low visual impact WiMAX
- Vertical or horizontal polarization
- Type N female connector
- · Stainless steel bracket and hardware

#### **APPLICATIONS**

- 2.4 GHz wireless LAN applications
- 802.11b/g client antennas

#### **SPECIFICATIONS**


| PARAMETER               |                                      |
|-------------------------|--------------------------------------|
| Frequency range         | 2400 to 2483 MHz                     |
| Gain                    | 12 dBi                               |
| Horizontal beamwidth    | 65°                                  |
| Vertical beamwidth      | 34°                                  |
| Front-to-back           | 25 dB                                |
| Input return loss (S11) | -14 dB                               |
| VSWR                    | 1.5:1                                |
| Impedance               | 50 ohm                               |
| Input power             | 100 W                                |
| Operating temperature   | -40°C to +70°C                       |
| Pole size               | 1 to 1.66 in<br>(25 mm to 39 mm)     |
| Weight                  | 13.5 oz (383 g)                      |
| Dimension (W x L x H)   | 4 x 4 x 4 in<br>(102 x 102 x 102 mm) |
| Bracket tilt            | 15°                                  |

#### **SYSTEM ORDERING**


MD24-12 2.4 GHz 12 dBi Mini Directional Antenna

#### **ANTENNA PATTERNS**

## Horizontal plane 2400 MHz



## Elevation plane 2400 MHz



Americas: +1.847 839.6925

IAS-AmericasEastSales@lairdtech.com

Europe: +44.1628.858941 IAS-EUSales@lairdtech.com

Asia: +86.21.5855.0827.127 IAS-AsiaSales@lairdtech.com

# **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Antennas category:

Click to view products by Laird Connectivity manufacturer:

Other Similar products are found below:

CCT FM1 ABFT AD-NM-SMAF 001-0021 CTC110 MAF94149 EXE902SF MMCX-SMA-100 PDQ24496-91NF GAN30084EU 930-033-R A08-HABUF-P5I AAF95035 DG-ANT-20DP-BG-B APAMPGJ-141 1513563-1 OF86315-FNF OP24516DS-91NM A09-HASM-7 EXE902MD EXE902SM SPDA17806/2170LAR APAMPG-117 GPS1575SP26-004 GPS15MGSMA CMD69273P-30NF CMQ69273-30NF RD2458-5-OTDR-NM RD2458-5-RSMA TRAB24/49003 W4120ER5000 W6102B0100 YE572113-30RSMM 108-00014-50 SPDA17RP918 OP24516SX-91NM OP24516SX-91RSMM CMQ69273P-30NF CMS69273-30NF CMS69273P-30NF TRAB24003N TRAB24003NP TRAB8213NP TRAB8903 A09-Y8NF A09-Y11NF A09-HSM-7 A09-F8NF-M A09-F5NF-M