

Battery Powered Milliohm Meter

High accuracy, high resolution portable Milliohm Meter
Battery operated for field use

Features:

- Four terminal Kelvin measurements
- Over-temperature and over-voltage protection
- 5 ranges with 100 μ max resolution
- Large 2000 count LCD display
- Auto-Hold and Auto power off
- Invalid test indicators prevent inaccurate measurements
- Built-in water resistant case with shoulder strap
- Complete with 8AA batteries, and 2 sets of test leads (4 wire with 4 alligator clips and 4 wire with 2 Kelvin alligator clips)



Kelvin alligator clips

Specifications	Range	Resolution	Current	Basic Accuracy
Resistance	200.0m	0.1m	100mA	$\pm(0.5\%rdg + 2 \text{ digits})$
	2000m	1m	100mA	$\pm(0.5\%rdg + 2 \text{ digits})$
	20.00	0.01	10mA	$\pm(0.5\%rdg + 2 \text{ digits})$
	200.0	0.1	10mA	$\pm(0.5\%rdg + 2 \text{ digits})$
	2000	1	1mA	$\pm(0.5\%rdg + 2 \text{ digits})$
Power	8 AA batteries			
Dimensions	9.8 x 7.5 x 4.3" (250 x 190 x 110mm)			
Weight	3.3lbs (1.5kg)			

Ordering Information:

- 380580.....Battery Powered Milliohm Meter
 380580-NIST380580 with Calibration Traceable to NIST
 380565.....Test Leads w/Kelvin clips for 380580



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Test Leads](#) category:

Click to view products by [Extech](#) manufacturer:

Other Similar products are found below :

[R928010000](#) [R928142000](#) [1301430020](#) [15101](#) [15115](#) [15117](#) [15301](#) [15303](#) [15304](#) [15102](#) [15120](#) [15308](#) [15408](#) [15302](#) [15306](#) [15307](#) [15502](#)
[15403](#) [15407](#) [15409](#) [15501](#) [15506](#) [EM3782-12-7#](#) [EM4702-12-0](#) [BU-1149-A-36-0](#) [BU-1481-E-12-0](#) [BU-1481-E-24-0](#) [2524-A-60](#) [924961-C](#)
[LB1F-2R-RED](#) [LB1F-2R-YLW](#) [2500](#) [2501](#) [2524-A-48](#) [2977-J-48](#) [R928051000](#) [R928141000](#) [R928143000](#) [R948131000](#) [BU-1449-E-12-2](#)
[BU-1480-E-24-0](#) [BU-1481-E-12-2](#) [BU-1481-E-24-2](#) [LB1F-2R-BLK](#) [LB1F-2R-BLUE](#) [EM3542-1#](#) [EM3782-12-8#](#) [6345](#) [6432](#) [72929-20-2](#)