

## Temperature Probes

Use with thermocouple thermometers and multimeters with Type K and Type J functions

### Bead Wire Type K and J Temperature Probes

- **TP870** .....Bead wire; 39" (1m) cable; subminiature Type K connector; (-40 to 482°F/-40 to 250°C);
- **872502**.....Bead Wire; 39" (1m) cable; subminiature Type J connector; Range (-40 to 392°F/-40 to 200°C)
- **TP873** .....Bead wire; 36" (.91m) cable; subminiature Type K with banana connector; Range (-22 to 572°F/-30 to 300°C)
- **TP873-5M**.....Bead wire; 16.4ft (5m) cable; subminiature Type K with banana connector; Range (-22 to 572°F/-30 to 300°C)
- **TP875** .....High temperature bead wire probe; 39" (1m) cable; subminiature Type K with banana connector; Range (-58 to 1000°F/-58 to 538°C)



TP870



872502



TP873



TP875

### Type K and J Temperature Probes

#### Penetration

- **TP882** ..... 5.9" (150mm) High Temperature Penetration Probe; Stainless steel 304; 72" (183cm) cable; probe diameter 0.13" (3.3mm); Type K, Range (-40 to 1000°F/-40 to 538°C)



TP882



871515

#### General Purpose

- **871515**.... 4" (100mm) General Purpose Probe; 39" (1m) cable; probe diameter 0.126" (3.2mm); Type K, Range (-40 to 1292°F/-40 to 700°C)
- **881605**.... 5.9" (150mm) General Purpose Probe; Stainless steel 316; 78.7" (200cm) coiled cable; probe diameter 0.126" (3.2mm); Type K, Range (-40 to 1472°F/-40 to 800°C)
- **801515**.... 4" (150mm) General Purpose Probe; 44" (112cm) cable; diameter 0.126" (3.2mm); Type J, Range (-40 to 842°F/-40 to 450°C)



881605



801515

#### Immersion

- **881603**.... 5.9" (150mm) Immersion Probe; Stainless steel 316; 78.7" (200cm) coiled cable; diameter 0.126" (3.2mm); Type K, Range (-40 to 1472°F/-40 to 800°C)

#### Surface

- **881602**.... 5.7" (144.7mm) Surface Probe; Stainless steel 304; 78.7" (200cm) coiled cable; diameter 0.314" (8mm); Type K, Range(-40 to 932°F/-40 to 500°C)
- **881616**.... Magnetized Type K Surface Probe with subminiature connector; 6' teflon cable with strain relief, 1" x 0.75" surface area; Range -40°F to 482°F (-40°C to 250°C); Includes replacement temperature element



881602



881603



881616

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Test Probes](#) category:*

*Click to view products by [Extech](#) manufacturer:*

Other Similar products are found below :

[6214](#) [6265](#) [6474](#) [815003](#) [923832-BK-B](#) [P-KIT-1](#) [R941850000](#) [925250-R](#) [72923-2](#) [923848-C](#) [973368101](#) [972318101](#) [972318100](#)  
[MXHQ87WJ3000](#) [66.9115-23](#) [TAS90](#) [VL1735/45](#) [973368100](#) [972327100](#) [972327101](#) [975017700](#) [975018700](#) [973995100](#) [973995101](#)  
[100039-080-958](#) [CT3986B-120](#) [CT3987B-120](#) [CT3983B-120](#) [CT3979B-150](#) [CT3981B-120](#) [CT3985B-120](#) [402-IEC-RT](#) [402-IEC-SW](#) [404-](#)  
[IEC-RT](#) [AX-CP-01-SET](#) [AX-CP-05-B](#) [AX-CP-05-R](#) [464-IEC-NEEDLE13/0,6-RT](#) [464-IEC-NEEDLE13/0,6-SW](#) [464-IEC-RT](#) [464-IEC-SW](#)  
[00043](#) [404-IEC-SW](#) [00125](#) [1445](#) [MPS1RT](#) [0602 4592](#) [0602 4892](#) [0628 0020](#) [606MG6-IEC-RT](#)