

Battery Powered Milliohm Meter

High accuracy, high resolution portable Milliohm Meter
Battery operated for field use

Features:

- Four terminal Kelvin measurements
- Over-temperature and over-voltage protection
- 5 ranges with 100 μ max resolution
- Large 2000 count LCD display
- Auto-Hold and Auto power off
- Invalid test indicators prevent inaccurate measurements
- Built-in water resistant case with shoulder strap
- Complete with 8AA batteries, and 2 sets of test leads (4 wire with 4 alligator clips and 4 wire with 2 Kelvin alligator clips)



Kelvin alligator clips

Specifications	Range	Resolution	Current	Basic Accuracy
Resistance	200.0m	0.1m	100mA	$\pm(0.5\%rdg + 2 \text{ digits})$
	2000m	1m	100mA	$\pm(0.5\%rdg + 2 \text{ digits})$
	20.00	0.01	10mA	$\pm(0.5\%rdg + 2 \text{ digits})$
	200.0	0.1	10mA	$\pm(0.5\%rdg + 2 \text{ digits})$
	2000	1	1mA	$\pm(0.5\%rdg + 2 \text{ digits})$
Power	8 AA batteries			
Dimensions	9.8 x 7.5 x 4.3" (250 x 190 x 110mm)			
Weight	3.3lbs (1.5kg)			

Ordering Information:

- 380580.....Battery Powered Milliohm Meter
 380580-NIST380580 with Calibration Traceable to NIST
 380565.....Test Leads w/Kelvin clips for 380580



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Digital Multimeters](#) category:

Click to view products by [Extech](#) manufacturer:

Other Similar products are found below :

[8009](#) [6111-517](#) [FS881](#) [40705X](#) [USB390A](#) [780417A](#) [GPT-9904](#) [382099](#) [589250](#) [780418](#) [C.A 6131](#) [C.A 6133](#) [30XR](#) [34XR](#) [35XP](#) [TESTO](#)
[745](#) [0590 7450](#) [TESTO 760-3](#) [0590 7603](#) [440012](#) [AX-155](#) [AX-174](#) [AX-178](#) [AX-18B](#) [AX-190A](#) [AX-503](#) [AX-507B](#) [AX-572](#) [AX-594](#) [AX-](#)
[LCR41A](#) [AX-MS8221A](#) [AX-MS8250](#) [AX-PDM01](#) [AX-T520](#) [AX-T901](#) [AX-T903](#) [BAT-250-EUR](#) [BM233](#) [BM805S](#) [BM807S](#) [BM817S](#)
[BM827S](#) [BM829S](#) [BM857S](#) [BM859S](#) [BM867S](#) [BM905S](#) [BM906S](#) [33XR](#) [UNITEST TESTFIX 9023](#) [37XR](#) [UT56](#)