SERIES




Ampheno

UNIVERSAL SERIAL BUS CONNECTORS







DESCRIPTION

The Amphenol UE27 and UE28 Series is a complete RoHS compliant interconnect solution designed in accordance with Universal Serial Bus Specification Version 2.0. USB is a suitable alternative for the various input/output interfaces used on personal computers and other consumer electronics, providing a single interface for all of your peripherals with the convenience of plug-and-play.

FEATUR<u>ES</u>

- Designed to USB specification version 2.0
- Plug-and-play eliminates the need to shut down the system to make modifications
- Metal shell for EMI shielding
- 4 position connector with 2mm centerline signal and
 2.5mm centerline power contacts
- Connector is polarized for proper termination

- Can be used with asynchronous and isochronous data transfer methods, supports data rates up to 480 Mbps
- RoHS compliant
- Outer power contact positions accept 20-24 AWG wire
- Signal contact positions accept 26-28 AWG wire
- High temperature material (<260° C) is available on select versions

SPECIFICATIONS

PHYSICAL CHARACTERISTICS

Housing Flammability

Rating: UL 94V-0 Housing Material: Thermoplastic

Shell Plating: Nickel over Copper alloy

Shell Material: Copper alloy Solder Tail Plating: Tin over Nickel Durability: 1500 mating cycles

Mating Force: 35 Newtons maximum

Unmating Force: 10 Newtons minimum

MECHANICAL CHARACTERISTICS

ELECTRICAL CHARACTERISTICS

Voltage Rating: 30 Vac (rms)

Current Rating: 1 Amp maximum per contact

Dielectric Withstanding

Voltage: 750 VAC at sea level

Insulation

Resistance: $1000 \text{ M}\Omega$ Capacitance: 2 pF maximum

Contact

Resistance: $30 \text{ m}\Omega$ maximum

ENVIRONMENTAL CHARACTERISTICS

Temperature

Rating: -55 to 85 degrees C

APPLICATIONS

PC/ Laptop
 Router
 Switch

Digital Camera
 Modem
 MP3 Player
 Printer
 Set-Top Box


CONTACT REEL SIZE


Crimp 20-24 AWG: 10,000 contactsCrimp 26-28 AWG: 20,000 contacts

CRIMP CONTACTS ARE NO LONGER AVAILABLE


Amphenol® Canada Corp. Telephone: (416) 754-5656 Facsimile: (416) 754-8668


TYPE A RECEPTACLE







RECOMMENDED P.C.B. LAYOUT (COMPONENT SIDE OF BOARD)






RECOMMENDED P.C.B. LAYOUT (COMPONENT SIDE OF BOARD)






UE27-AEX4-X0X

RECOMMENDED P.C.B. LAYOUT (COMPONENT SIDE OF BOARD)







UE27-AMX4-X0H

RECOMMENDED P.C.B. LAYOUT (COMPONENT SIDE OF BOARD)

TYPE B RECEPTACLE






RECOMMENDED P.C.B. LAYOUT (COMPONENT SIDE OF BOARD)


TYPE A PLUG

TYPE B PLUG




CONTACTS (CRIMP) No Longer Available





UE28-CKXØ-ØØØ

HOW TO ORDER RECEPTACLE



HOW TO ORDER PLUG UF28- XMX4 - XX0 **SERIES MODIFIER** UE28 - ROHS COMPLIANT PLUG KIT 0 - STANDARD TYPE SHELL STYLE A - SERIES A (PRE-LOADED SOLDER CUP OR UNLOADED CRIMP) 2 - SMALL REAR CLAMP (3.2-4.0)(A-TYPE ONLY) B - SERIES B (PRE-LOADED SOLDER CUP OR UNLOADED CRIMP) 3 - LARGE REAR CLAMP (4.2-5.0) (STANDARD) CONTACT TYPE/ KIT TYPE HOUSING COLOUR M - SOLDER CUP (HOUSING INCLUDES PRE-LOADED CONTACTS) 1 - BLACK (STANDARD) 2 - BEIGE HOUSING/CONTACTS CONTACT PLATING 4 - 4 PRE-LOADED SOLDER CUP CONTACTS

Amphenol[®]

5 - 30μ" GOLD (STANDARD) 7 - GOLD FLASH

Commercial Products

605 Milner Ave. Toronto, Ontario Canada M1B 5X6

Telephone: (416) 754-5656 Facsimile: (416) 754-8668 E-Mail: sales@amphenolcanada.com Website: www.amphenolcanada.com © Amphenol Canada Corp.

Specifications subject to change without notice.

Printed in Canada 08/98 (Electronically modified 04/07)

Designed by K. Jasper Marketing Communications Inc.

CATALOGUE NR. ADT 0002

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for USB Connectors category:

Click to view products by Amphenol manufacturer:

Other Similar products are found below:

10033527-N3112MLF 17-210561 GMCB05B11124H1EU 17-200931 65-647-8-BK-BU 690-010-295-484 73725-1191BLF 950 E8144-B01021-L A-USB A-LP-SMT-C A-USB B-TOP-C MUSBA511N5 MUSBB15131 MUSBC111M5 MUSBD11135 217450-1 CA 6 W LD 896-30-004-00-000000 KUSBVX-BS1N-W30 KUSBX-AP-KIT-SCBLK KUSBX-AS2N-W KUSBX-SMT2AP1S-W KUSBX-SMT8S1NBTR 30-498-6 SK-60A-2 17-200261 17-210051 1734082-1 FK-37-32SL 30-1574 30-470 30-489 30-572-3 30-9503 M9177/2-1 MAB 5 S MIKROE-1451 33UBBR-04SW11R USBFTV2PEM2G USBFTVC6ZN USBFTVSCCG KUSBX-AS2N-W30 KUSBX-SLAS1N-W KUSBX-SLAS1N-W30 1-1734084-2 E8110-001-01 MUSBC11135 NK-27-32SL 33UBAR-04SW11 USBF21ZNSCC