

## EasyView™ Dual Input Thermometers

**Choice of Basic Type K or Datalogger model**  
 Datalogger model (EA15) compatible with 7 Types of Thermocouples

### Features:

- Compact and rugged design features large backlit display
- Displays [T1 plus T2] or [T1-T2 plus T1] or [T1-T2 plus T2]
- Selectable units of °F, °C, K (Kelvin)
- Wide temperature range with 0.1°/1° resolution
- Timer function displays elapsed time plus the time when MIN and MAX readings are taken
- Data Hold function freezes reading on display
- Auto Power off to save battery life
- Low battery and overrange indication
- Records Max/Min readings for later recall
- Complete with built-in stand, protective holster, two Type K bead wire temperature probes (-22 to 572°F/-30 to 300°C), and 6 AAA batteries



EA10 Type K Dual Input Thermometer

EA15 Dual Input, 7 Thermocouple Type Thermometer Datalogger. Software included

### Model EA10

#### Features:

- Basic Type K Dual input
- OFFSET key used for zero function to make relative measurements

### Model EA15

#### Features:

- Dual input accepts Types J, K, E, T, R, S, and N thermocouples
- Built-in datalogger stores up to 8800 data sets
- RS-232 port to transfer data to PC for analysis
- Real Time Clock
- Includes Windows<sup>®</sup> 95/98/NT/2000/ME/XP/7 compatible software and cable

Specifications	EA10	EA15
Thermocouple Type	EA10	EA15
J	—	-200 to 1994°F (-150 to 1090°C)
K	-200 to 1999°F (-200 to 1360°C)	-200 to 1999.9°F (-150 to 1370°C)
T	—	-200 to 752°F (-150 to 400°C)
E	—	-200 to 1598°F (-150 to 870°C)
R	—	35 to 1999.9°F (2 to 1767°C)
S	—	35 to 1999.9°F (2 to 1767°C)
N	—	-200 to 1999.9°F (-150 to 1300°C)
Resolution	0.1°	0.1°
Basic Accuracy	±0.3% (+2°F/+1°C)	±0.05% rdg (+1.5°F/+0.75°C) Types J,K,E,T,N ±0.05% rdg (+4°F/+2°C) Types R,S
Dimensions	6 x 2.8 x 1.5" (152 x 72 x 37mm)	6 x 2.8 x 1.5" (152 x 72 x 37mm)
Weight	8.3oz (235g)	8.3oz (235g)

### Ordering Information:

- EA10 .....EasyView<sup>®</sup> Dual K Thermometer
- EA10-NIST .....EA10 with Certificate of Calibration Traceable to NIST
- EA15 .....EasyView<sup>®</sup> Dual Input 7 Thermocouple Type Temperature Datalogger
- EA15-NIST .....EA15 with Certificate of Calibration Traceable to NIST
- 409996 .....Soft Vinyl Pouch

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Environmental Test Equipment](#) category:*

*Click to view products by [Extech](#) manufacturer:*

Other Similar products are found below :

[CW40](#) [F150C10E3DRT](#) [F150LTC20](#) [F150CD10E2](#) [F150L75](#) [F150LRS](#) [S-11](#) [FLUKE-LDG](#) [382153](#) [FM100](#) [RH210](#) [382253](#) [MO290-P](#)  
[GEO-CABLE-REEL-50M](#) [T197914](#) [RD300-L](#) [IR11BD](#) [IR11GM](#) [IR12GM](#) [IR21BD](#) [IR31CE](#) [IR32BC](#) [IR33BC](#) [MP7217TC](#) [NGM-1](#) [SGX-](#)  
[7NH3](#) [UT381](#) [F150-SLC50](#) [AW-CO-1000](#) [AW-NmHc-100](#) [3.000.401](#) [AX-7535](#) [CS-9S6SS-A](#) [P 2800 A](#) [P 2801](#) [P 2802](#) [P 5039](#) [P 5130](#) [P](#)  
[5055](#) [P 5060](#) [P 5065](#) [P 5086](#) [P 5090](#) [P 5110](#) [P 5115](#) [P 5135](#) [P 5140](#) [P 5145](#) [P 5150](#) [P 5160](#)