



RH/Temperature Pen

Compact, Digital Hygro-Thermometer Ideal for field use

Features:

- Dual LCD display for Temperature, Humidity, and advanced function indication
- Measures Temperature (°C/°F) and Relative Humidity simultaneously
- Built-in Temperature and Humidity sensors for convenient operation
- Max/Min memory functions for both Temperature & Relative Humidity
- Built-in self calibration utility with optional RH calibration bottles
- Data Hold for freezing the LCD display status
- Complete with pocket clip and 3V lithium battery
- Optional kit includes 33% and 75% RH Calibration Standards and hard vinyl carrying case





Specifications	% Relative Humidity	Temperature
Range	10 to 90%	14 to 122°F (-10 to 50°C)
Accuracy	±5%	±1.8°F/1°C
Resolution	0.1%RH	0.1°C or °F
Power	One lithium battery (CR2032)	
Dimensions	5.7x 1.2 x 1" (145 x 30 x 25mm)	
Weight	2.3 oz.(65g)	

Ordering Information:

445580	RH/Temperature Pen
445580-NIST	445580 with Calibration Traceable to NIST.
RH300-CAL	33% and 75% RH calibration reference

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Clamp Multimeters & Accessories category:

Click to view products by Extech manufacturer:

Other Similar products are found below:

I800 FLUKE 1630-2 ZAPDUMOD-03 ZARKMS-01-99 UT233 TESTO 770-3 0590 7703 AX-3550 AX-M266C BM079 BM089 BM157 BM162 BM197 KEW2210R FLUKE 80I-110S FLUKE I200 FLUKE I200S FLUKE I3000FLEX-24 FLUKE I310S FLUKE I400 CIE600 TESTO 770-2 0590 7702 34194A KEW2433R KEW8112 FLUKE 772 380976-K MA3110 MA440 MA443 MA445 FLUKE-374 FC TA74 AMP-320 CM55 CM46 I200 ACD-6 PRO FLUKE-1630-2FC I410 CM44 CM42 FLK-A3000 FC FLUKE-376 FC ACD-14-PRO MA610 F201 F205 MA193 (250 MM) DIGIFLEX 4000A 350MM