



Dual Laser InfraRed Thermometers

Dual Laser Targeting

['] Indicates ideal measuring distance. Choose from 12" or 30" distance model where two laser points converge to 1" target spot

Features:

- Dual laser for accurate target
- White backlit dual LCD display
- Fast 0.15 second response time with Max display
- Adjustable emissivity increases measurement accuracy for different surface
- Adjustable High/Low set points with audible alarm alerts user when temperature exceeds the programmed set points
- Lock function for continuous readings
- Double molded housing
- Complete with pouch case and 9V battery



Fast response captures hot spots



Max hold indicates and holds the peak temperature for easy identification of hot spots



Two laser points converge at a distance of 30"/76.2cm (model 42512) or 12"/30.5cm (model 42511) and form a 1" (2.5cm) spot.



Ordering Information:

4251112" distance Dual Laser InfraRed Thermometer

42512-NIST....30" dist. Dual Laser InfraRed Thermometer w/ Calibration Traceable to NIST.



Dual Laser

Our Fastest and Easiest-to-use IR Thermometer

✓ Dual lasers identify exact

measuring spot when they converge to a single spot

✓ 30" or 12" distance models

✓ Fast response is ideal for

ture

quick checks of multiple spots in a process or for catching spikes in tempera-

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Environmental Test Equipment category:

Click to view products by Extech manufacturer:

Other Similar products are found below :

 CW40
 F150C10E3DRT
 F150LTC20
 F150CD10E2
 F150L75
 F150LRS
 S-11
 FLUKE-LDG
 382153
 FM100
 RH210
 382253
 MO290-P

 GEO-CABLE-REEL-50M
 T197914
 RD300-L
 IR11BD
 IR11GM
 IR21BD
 IR31CE
 IR32BC
 IR33BC
 MP7217TC
 NGM-1
 SGX

 7NH3
 UT381
 F150-SLC50
 AW-CO-1000
 AW-NmHc-100
 3.000.401
 AX-7535
 CS-9S6SS-A
 P 2800 A
 P 2801
 P 2802
 P 5039
 P 5130
 P

 5055
 P 5060
 P 5065
 P 5086
 P 5090
 P 5115
 P 5135
 P 5140
 P 5145
 P 5150
 P 5160