

Tpcm[™] AL52

Tpcm[™] AL52 is a thermally conductive phase change material coated on both sides of aluminum foil. At temperatures greater than 52°C, Tpcm[™] AL52 changes into a molten state and, under low closure force, wets the heat sink and component surfaces to create a very thin, low thermal resistance interface. Tpcm[™] AL52 has great heat spreading characteristics and won't flow from the interface. Tpcm[™] AL52 has superior thermal performance comparable to the highest performing grease and phase change products available. Since it is a free standing film it is easy to handle and is a great replacement for messy grease.

Tpcm[™] AL52 is available as die cut parts or sheets. Tpcm[™] AL52 is available with or without adhesive.

Typical Properties	
Color	Gray
Thickness Inches (millimeters)	0.003" (0.076mm)
Standard Coating Thickness per side	0.0005" (0.013mm)
Density	2.1 g/cc
Shelf Life	Indefinite
UL Flammability Rating	94 V0
Maximum Use Temperature	200°C
Phase Change Softening Temperature	52°C
Thermal Impedance	
5 psi	0.03 °C-in²/ W
34.5 Kpa)	0.193 °C-cm ² /W

Thermaphase® is a registered trademark of Laird U.S. Patent Numbers 5,930,893 and 6,286,212

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Thermal Interface Products category:

Click to view products by Laird Connectivity manufacturer:

Other Similar products are found below:

63072-2-4013 64442-1-7612 FGN80-2 PFM-172-60 95778-1-5171 A-40 ACDIN4001-01-S APA502-80-001 188761F00000G 95779-15171 9601-7 9614-2-4013 189790F00000 189951F00000G 2103-4-7320 CN9565-000 31570-2-4013 LZ24-1 LZ30-9 4103G 450-20-0025
5300AC 1.500G 53-77-13ACG 450-20-0017 4949G 08121 08133 08151 08188 08196 54476-2-4013 71883-2-4053 188651F00000G
64445-1-7612 TVQF-1225-07S 66786-4-7320 TP0001 4952G 4860 450-20-0148 88601-2-2929 SC80-W2 09450-M45 09362-M45
V6516C A17713-05 A17690-06 A17690-10 A17690-05 A17690-03