

EC210 Compact Conductivity/TDS Meter



Compact handheld Conductivity Meter with long life carbon rod combination electrode measures Conductivity, TDS and Temperature. Units of measure include μ S/cm, mS/cm, ppm, °F, and °C. The meter features three ranges for Conductivity and TDS plus adjustable Temperature compensation factor to maintain accuracy.

Applications:

- Wastewater and drinking water analysis
- Environmental tests to determine the health of ponds, streams, wells, and other bodies of water
- Manufacturing processes such as component or PCB rinsing



Features

- Simultaneous display of Conductivity or TDS with Temperature
- Automatic Temperature Compensation
- Temperature compensation factor adjustable between 0 to 5.0% per °C
- Min/Max and Data Hold functions
- Auto Power Off with disable feature

- Use optional 1413µS Conductivity Standard (EC-1413-P) for calibration
- Complete with Conductivity cell and 39" (1m) cable,
 9V battery, and soft case

Specifications	Ranges	Max Resolution	Basic Accuracy
Conductivity	2000µS/cm	1µS/cm	±2% FS
	20mS/cm	0.01mS/cm	
	100mS/cm	0.1mS/cm	
TDS	1200ppm	1ppm	±2% FS
	12,000ppm	10ppm	
	66,000ppm	100ppm	
Temperature	32 to 122°F (0 to 50°C)	0.1°F/°C	±1.5°F/0.8°C
Dimensions	Meter: 5.3 x 2.4 x 1.3" (135 x 60 x 33mm); Probe: 0.9" (22mm)D x 4.7" (120mm)L		
Weight	10.4oz (295g) includes probe and battery		

Ordering

EC210......Conductivity/TDS Meter

EC-1413-P...... 1413µS Conductivity Standard (2 bottles - 1 pint each)

0-4-: 7000000000100

UPC Code: 793950052105

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Environmental Test Equipment category:

Click to view products by Extech manufacturer:

Other Similar products are found below:

CW40 F150C10E3DRT F150LTC20 F150CD10E2 F150L75 F150LRS S-11 FLUKE-LDG 382153 FM100 RH210 382253 MO290-P

GEO-CABLE-REEL-50M T197914 RD300-L IR11BD IR11GM IR12GM IR21BD IR31CE IR32BC IR33BC MP7217TC NGM-1 SGX
7NH3 UT381 F150-SLC50 AW-CO-1000 AW-NmHc-100 3.000.401 AX-7535 CS-9S6SS-A P 2800 A P 2801 P 2802 P 5039 P 5130 P

5055 P 5060 P 5065 P 5086 P 5090 P 5110 P 5115 P 5135 P 5140 P 5145 P 5150 P 5160