

1000A Clamp Meters with IR Thermometers

Clamp-on multimeter with built-in non-contact InfraRed Thermometer

Ideal for industrial applications the 800 series Full size 1000A clamps feature a built-in Infrared thermometer and rugged double molded housing.

EX800 Series Features:

- Non-contact InfraRed Temperature measurements with laser pointer
- Models with True RMS Current and Voltage measurements
- Peak hold captures inrush currents and Transients
- MultiMeter functions include AC/DC Voltage, Resistance, Capacitance, Frequency, Type K Temperature (EX820/EX830), Diode, and Continuity
- 1.7" (43mm) jaw opening for conductors up to 750MCM or two 500MCM
- 4000 count backlit display
- Features include Data Hold and Min/Max
- Autoranging with manual range button
- Auto Power off
- Complete with test leads, 9V battery, general purpose Type K probe (EX820/EX830), and case

Model EX810

- AC Current
- Average responding

Model EX820

- AC Current
- True RMS
- Type K thermometer

Model EX830

- DC/ AC Current
- True RMS
- Type K thermometer
- DC Zero



BUILT IN IR Thermometer



True RMS meter gives you accurate readings of non-sinusoidal waveforms.



Built-in IR Thermometer with laser pointer is an excellent troubleshooter for locating hot spots and overheating motors.

Specifications	EX810	EX820	EX830	Basic Accuracy
IR Temperature (IR)	-58 to 518°F -50 to 270°C	-58 to 518°F -50 to 270°C	-58 to 518°F -50 to 270°C	±2.0% rdg or ±4°F/±2°C
AC Current	0.1 to 1000A	0.1 to 1000A	0.1 to 1000A	±2.8% (EX810); ±2.5% (EX820, EX830)
DC Current	—	—	0.1 to 1000A	±2.5%
AC Voltage	0.1mV to 600V	0.1mV to 600V	0.1mV to 600V	±1.8% (EX810); ±1.5% (EX820, EX830)
DC Voltage	0.1mV to 600V	0.1mV to 600V	0.1mV to 600V	±1.5%
Resistance	0.1 to 40MΩ	0.1 to 40MΩ	0.1 to 40MΩ	±1.5%
Capacitance	0.001nF to 40,000μF	0.001nF to 40,000μF	0.001nF to 40,000μF	±3.0%
Frequency	0.001kHz to 4kHz	0.001kHz to 4kHz	0.001kHz to 4kHz	±1.5%
Type K Temperature	—	-4 to 1400°F -20 to 760°C	-4 to 1400°F -20 to 760°C	±(3%rdg+9°F/5°C)
Continuity	Yes	Yes	Yes	
Inrush	Yes	Yes	Yes	
Diode	Yes	Yes	Yes	
Dimensions	0.6x4.3x2" (270x110x50mm)	10.6x4.3x2" (270x110x50mm)	10.6x4.3x2" (270x110x50mm)	
Weight	13.6oz (386g)	13.6oz (386g)	13.6oz (386g)	

Ordering Information:

- EX8101000A AC Clamp/DMM+IR Thermometer
 EX810-NISTL*1000A AC Clamp/DMM+IR Thermometer w/ Calibration Traceable to NIST
 EX8201000A AC True RMS Clamp/DMM+IR Thermometer
 EX820-NISTL*1000A AC True RMS Clamp/DMM+IR Thermometer w/ Calibration Traceable to NIST
 EX8301000A AC/DC True RMS Clamp/DMM+IR Thermometer
 EX830-NISTL*1000A AC/DC True RMS Clamp/DMM+IR Thermometer w/ Calibration Traceable to NIST

*NISTL is a Limited NIST: Product is certified to all functions except IR Thermometer



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Clamp Multimeters & Accessories](#) category:

Click to view products by [Extech](#) manufacturer:

Other Similar products are found below :

[FLUKE 1630-2](#) [ZAPDUMOD-03](#) [ZARKMS-01-99](#) [UT233](#) [TESTO 770-3](#) [0590 7703](#) [AX-3550](#) [AX-M266C](#) [BM079](#) [BM089](#) [BM157](#)
[BM162](#) [BM197](#) [KEW2210R](#) [FLUKE 80I-110S](#) [FLUKE A3002FC](#) [FLUKE I200](#) [FLUKE I200S](#) [FLUKE I3000FLEX-24](#) [FLUKE I310S](#)
[CIE600](#) [TESTO 770-2](#) [0590 7702](#) [34194A](#) [KEW2433R](#) [KEW8112](#) [FLUKE 772](#) [380976-K](#) [MA3110](#) [MA440](#) [MA443](#) [MA445](#) [FLUKE-374](#)
[FC](#) [TA74](#) [AMP-320](#) [CM55](#) [CM46](#) [I200](#) [ACD-6 PRO](#) [FLUKE-1630-2FC](#) [CM44](#) [CM42](#) [FLK-A3000 FC](#) [FLUKE-376 FC](#) [MA610](#) [EA30-](#)
[NIST](#) [F201](#) [F205](#) [MA193 \(250 MM\)](#) [DIGIFLEX 4000A 350MM](#) [DIGIFLEX 400A 170MM](#) [DIGIFLEX 400A 250MM](#)