		Т		G	П	т		0	D	>	
				Unit: mm			\$ <u>6.90</u>			<u>7,9</u> ③ <u>2,84</u>	<b>_</b>
2	Angle	DIM	××	TOLER X.	2		2,84	r		В 2,77 А	2
ω	±5° Id. Modification		<u>±0.30</u> <sup>③</sup> <sup>Update</sup> ±0.20 <sup>②</sup> <sup>Update</sup>	<ul><li>⊕ €</li></ul>			1,42	UNC4#40		6,0 6,0	သ
4	Date	26.10.2012 Winnie	01.04.2013 Winnie 28.01.2013 Winnie	24.04.2013			1,385 2,77 2,84 2,96		3±0,38 <b>©</b>	<u>     </u>	4
J	• WVSW/ components	ASSMA	e Approved 15.08.2014 e	Drawn				Operation void Current rating Contact resis Insulation res Dielectric with Operating ter Order Code:	CONTACT PI Contact area: Solder tails: 1 Shell plateing: Underplate: 5	SPECIFICAT MATERIAL Insulator: PB Contacts: Co	თ
6	nents Replace	ASS 49	Winnie AssMANN WSW-No. A-DD XX X-X		54.80	Dimensions PosiTion A B 9 16.30 25.00 15 24.60 33.30 25 38.30 47.10	2. Male Franke 3. Formale Male 4. Formale Formale Dim X 8. 15.875mm 09./15./25./37	Operation vorte Current rating: 3 Amps max. Contract resistance: 25 mohms max. Insulation resistance: 3000 Mohms min @ 500 VDC Dielectric withstanding voltage: 1000 VAC / minute Operating temperature: $-55^{\circ}C \sim +105^{\circ}C$ Order Code: A-DD xx - x - x T T T MaterMate	Rivet,Boardlock: Copper alloy CONTACT PLATING Contact area: Gold flash Solder tails: 100u" Tin over 40u" Nickel Shell plating: Tin plated Underplate: 50u" Nickel El ECTRICAL	SPECIFICATION MATERIAL Insulator: PBT, rated UL94V-0 , black Contacts: Copper alloy	0
7	Sheet 1/1	4956 CO rev05			69.4	C D Ø   0 30.8 16.92   0 39.2 25.25   0 43.1 38.96		nute			7
		T		ດ	п	п	D	C	σ		

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for D-Sub Standard Connectors category:

Click to view products by Assmann manufacturer:

Other Similar products are found below :

DCM37S732N DAM15P500 DEV09S364GTLF DEM09P032N DDM50P732N DAM15S332N 173109-2218 173109-2466 173109-2436 173109-2435 56F706-005-LI 56F711-015 015-0341-000 015-0372-008 015-8544-011 017041-0005 020419-0104 012-0515-000 012-9507-034 012-9507-114 012-9534-001 020745-0008 609-25P M24308/2-23Z M243082310F M243082410F M243082411F M24308/4-21 CT1A18-11PSA206 CT1N36-5SC CT2-16S-17PS CT2-20-15PCAU CT2-24-12PS CT2-24-28PSF127A206 CT2-32-9PC CT6F9767-14-4-14S-5PC CT6FA10SL-4PS CT7-18-10SC CT7-18-10SCAU CT7-18-12SCAU CT7-18-1PC CT7-18-1PCAU CT7-18-21SCAU M83513/01-FC M83723/76W24619 L/C M85049/48-3-2F 69001-865 6STD09PCM99B70X 6STD09SCM99B30X 6STD09SCT99S40X