Data Sheet

RF TERMINATION Type 65_N-75-0-11/133_N

Description

Standard Termination, Low Power



Product Configuration

Connector N plug (male)

Interface standards IEC 60169-16_MIL-STD-348A/304_CECC 22210

Technical Data

Electrical Data

Nominal Impedance 75 Ω Frequency range 0 to 1.3 GHz

Frequency sub range DC to 1 GHz 1 to 1.3 GHz VSWR max. 1.05 1.08

Power rating 1 Watt average power up to 30 °C ambient temperature, linearly derated to 0 Watt at 130 °C ambient

temperature.

1500 Watt peak power

Mechanical Data

Weight 0.044 kg

Environmental Data

Operating temperature -40 °C to 130 °C 2011/65/EU (RoHS) compliant

Material Data

Piece Part	Material	Surface Plating
Centre contact	Brass	Gold Plating (Nickel underplated)
Outer contact	Brass	SUCOPLATE (R) Plating
Body	Brass	SUCOPLATE (R) Plating
Insulator	PFA / PTFE	
Coupling nut	Brass	SUCOPLATE (R) Plating

Ordering Information

Single Packaging Packaging 65_N-75-0-11/133_NE

HUBER+SUHNER is certified according to ISO 9001, ISO 14001, AS/EN9100, ISO/TS 16949 and IRIS

www.hubersuhner.com

Waiver: Fact and figures herein are for information only and do not represent any warranty of any kind.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for RF Terminators category:

Click to view products by Huber & Suhner manufacturer:

Other Similar products are found below:

M39030/3-09S M39030/3-01S M39030/3-04N M39030/3-11N M39030/3-11S TNA2-50 TNGFL1-1-78 R4042N5000 32S17B-1.0E3

28S1ER-001N5 NF-C-1(40) 53S1RR-001N3 142275 56S1RR-001N4 18S15R-0.5E3 65_BNC-50-0-7/133_NE 71S1RR-001N4 02S17R001D3 6500.19.A R404240120 HT-50-1(40) NF-A-PJ-1(40) R404260000 NF-TMJ-P(50) HT-10-2 000-1075 DCA-17-01 27-9245

M85049/124-13N R4041D1000 1-221629-6 SF8015-6007 R4041D2121 R4041D2000 R4041D1121 65010_N-50-1/199_NE 65_N-75-011/133_NE SF8016-6404 6550.17.AA 65_N-50-0-51/113_NE 65_BNC-50-0-2/133_NE 6560.41.AA 65_QMA-50-0-4/111_NE 65_N-50-01/133_NE 65002_N-50-1/122_NE 65_SMB-50-0-31/111_NE 65_BNC-50-0-6/113_NE 2702702 1100.19.0001 6701.01.B