


# PCI-1710U/UL

# PCI-1710HGU

100 kS/s, 12-bit, 16-ch Universal PCI Multifunction DAQ Card

100 kS/s, 12-bit, 16-ch Universal PCI Multifunction DAQ Card with High Gain



FCC CE RoHS

## Features

- 16-ch single-ended or 8-ch differential or a combination of analog input
- 12-bit A/D converter, with up to 100 kHz sampling rate
- Programmable gain
- Automatic channel/gain scanning
- Onboard FIFO memory (4,096 samples)
- Two 12-bit analog output channels (PCI-1710U/HGU only)
- 16-ch digital input and 16-ch digital output
- Onboard programmable counter
- BoardID™ switch

## Specifications

### Analog Input

- Channels** 16 single-ended/ 8 differential (software programmable)
- Resolution** 12 bits
- FIFO Size** 4,096 samples
- Overvoltage Protection** 30Vp-p
- Input Impedance** 1 GΩ
- Sampling Modes** Software, onboard programmable pacer and external
- Input Range (V, software programmable) & Absolute Accuracy**

PCI-1710U/UL					
Gain	0.5	1	2	4	8
<b>Bipolar</b>	±10	±5	±2.5	±1.25	±0.625
<b>Unipolar</b>	N/A	0 ~ 10	0 ~ 5	0 ~ 2.5	0 ~ 1.25
<b>Absolute Accuracy (% of FSR)*</b>	0.1	0.1	0.2	0.2	0.4

PCI-1710HGU								
Gain	0.5	1	5	10	50	100	500	1000
<b>Bipolar</b>	±10	±5	±1	±0.5	±0.1	±0.05	±0.01	±0.005
<b>Unipolar</b>	N/A	0 ~ 10	N/A	0 ~ 1	N/A	0 ~ 0.1	N/A	0 ~ 0.01
<b>Absolute Accuracy (% of FSR)*</b>	0.1	0.1	0.2	0.2	0.4	0.4	0.8	0.8

\* ±1 LSB is added as the derivative for absolute accuracy

### Maximum Sampling Rate

Model	Gain	Max. Sampling Rate
PCI-1710U/UL	0.5, 1, 2, 4, 8	100 kS/s
PCI-1710HGU	0.5, 1	100 kS/s
	5, 10	35 kS/s
	20, 100	7 kS/s
	500, 1000	770 S/s

Note: The sampling rate for each channels will be affected by used channel number. For example, if 4 channels of PCI-1710U are used, the sampling rate is 100k/4 = 25 kS/s per channel.

### Analog Output (PCI-1710U/HGU only)

- Channels** 2
- Resolution** 12 bits
- Output Rate** Static update
- Output Range** (Software programmable)

Internal Reference	Unipolar	0 ~ 5 V 0 ~ 10 V
<b>External Reference</b>		0 ~ +x V @ -x V (-10 ≤ x ≤ 10)

- Slew Rate** 10 V/μs
- Driving Capability** 3 mA
- Operation Mode** Static update
- Accuracy** INLE: ±1 LSB, DNLE: ±1 LSB

### Digital Input

- Channels** 16
- Compatibility** 5 V/TTL
- Input Voltage** Logic 0: 0.8 V max.  
Logic 1: 2.0 V min.

### Digital Output

- Channels** 16
- Compatibility** 5 V/TTL
- Output Voltage** Logic 0: 0.4 V max.  
Logic 1: 2.4 V min.  
Sink: 8.0 mA @ 0.8 V  
Source: 0.4 mA @ 2.0 V
- Output Capability**

### Pacer/Counter

- Channels** 1
- Resolution** 16 bits
- Compatibility** 5 V/TTL
- Max. Input Frequency** 1 MHz

### General

- Bus Type** Universal PCI V2.2
- I/O Connector** 1 x 68-pin SCSI female connector
- Dimensions (L x H)** 175 x 100 mm (6.9" x 3.9")
- Power Consumption** Typical: 5 V @ 850 mA  
Max.: 5 V @ 1.0 A
- Operating Temperature** 0 ~ 60°C (32 ~ 140°F)
- Storage Temperature** -20 ~ 70°C (-4 ~ 158°F)
- Storage Humidity** 5 ~ 95% RH non-condensing

## Ordering Information

- PCI-1710U** 100 kS/s, 12-bit Multifunction Card
- PCI-1710UL** 100 kS/s, 12-bit Multifunction Card w/o AO
- PCI-1710HGU** 100 kS/s, 12-bit High-gain Multifunction Card

### Accessories

- PCLD-8710** DIN-rail Wiring Board w/ CJC
- PCL-10168-1E** 68-pin SCSI Shielded Cable, 1 m
- PCL-10168-2E** 68-pin SCSI Shielded Cable, 2 m
- ADAM-3968** 68-pin DIN-rail SCSI Wiring Board

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Data Logging & Acquisition](#) category:*

*Click to view products by [Advantech](#) manufacturer:*

Other Similar products are found below :

[ND-6063](#) [PCI-9221](#) [PCIE-7248](#) [ND-6017](#) [PCI-7432HIR](#) [DAQe-2214](#) [PCI-9113A](#) [ND-6053](#) [ACL-8112PG](#) [cPCI-7433](#) [cPCI-6208V-GL](#)  
[DAQe-2213](#) [ND-6056](#) [DAQ-2006](#) [DAQe-2502](#) [DAQ-2208](#) [PCIE-8560](#) [DAQe-2501](#) [PCI-7233](#) [PCM-7250+](#) [PCI-8124-C](#) [ND-6060](#) [DAQ-](#)  
[2206](#) [PCM-7248+](#) [PCIE-7200](#) [PCIE-PXI-EXP-KIT](#) [PCIE-7256](#) [PCIE-1884-AE](#) [USB-4761-BE](#) [PCI-1761-BE](#) [PCI-1711UL-CE](#) [PCI-1762-BE](#)  
[RHT30](#) [TH30](#) [USB-4702-AE](#) [USB-4704-AE](#) [USB-4711A-AE](#) [USB-4716-AE](#) [USB-4718-AE](#) [USB-4750-BE](#) [USB-4751-AE](#) [RHT35](#) [PCI-](#)  
[1714U-BE](#) [PCIE-1810-AE](#) [LPCIE-7250](#) [USB-4751L-AE](#) [PCI-1760U-BE](#) [PCI-6216V-GL](#) [LPCIE-7230](#) [PCI-1742U-AE](#)