

# ALGaInP Visible Laser Diode **ADL-66201TL**

DATE:2005/9/9 Ver 1.0

★660nm 20mW 60°C

**Reliable High Power Operation**

PRELIMINARY

**•Features**




1. Low operating current
2. High efficiency
3. High precision package
4. High power operation

**•Applications**


1. Laser pointers
2. Industrial laser markers / measuring instruments
3. High visibility applications

**•Absolute maximum ratings**

Parameter	Symbol	Condition	Rating	Unit
Light output power	P <sub>O</sub>	CW	22	mW
Reverse voltage (LD)	V <sub>RL</sub>	-	2	V
Reverse voltage (PD)	V <sub>RD</sub>	-	30	V
Forward current (PD)	I <sub>FD</sub>	-	10	mA
Case temperature	T <sub>C</sub>	-	-10~+60	°C
Storage temperature	T <sub>S</sub>	-	-40~+85	°C



( ) denoted typical value



**•Electrical and optical characteristics (T<sub>c</sub>=22.5±2°C)**

Parameter	Symbol	Min.	Typ.	Max.	Unit	Conditions
Peak wavelength	λ	650	658	665	nm	P <sub>o</sub> =20mW
Threshold current	I <sub>th</sub>		42	50	mA	
Operating current	I <sub>op</sub>		70	75	mA	P <sub>o</sub> =20mW
Operating voltage	V <sub>op</sub>	2.0	2.3	2.5	V	P <sub>o</sub> =20mW
Differential efficiency	η	0.5	0.8	1.0	mW/mA	P <sub>o</sub> =15~20mW
Monitor current	I <sub>m</sub>	0.05	0.15	0.5	mA	P <sub>o</sub> =20mW, V <sub>RD</sub> =0V
Parallel divergence angle	θ <sub>  </sub>	6	7	10	deg	P <sub>o</sub> =20mW
Perpendicular divergence angle	θ <sub>⊥</sub>	13	16	22	deg	
Parallel FFP deviation angle	Δθ <sub>  </sub>	-2	0	+2	deg	
Perpendicular FFP deviation angle	Δθ <sub>⊥</sub>	-2	0	+2	deg	
Emission point accuracy	ΔxΔyΔz	-80	0	+80	um	

**•Precautions**

- Do not operate the device above maximum ratings. Doing so may cause unexpected and permanent damage to the device.
- Take precautions to avoid electrostatic discharge and/or momentary power spikes. A change in the characteristics of the laser or premature failure may result.
- Proper heat sinking of the device assures stability and lifetime. Always ensure that maximum operating temperatures are not exceeded.
- Observing visible or invisible laser beams with the human eye directly, or indirectly, can cause permanent damage. Use a camera to observe the laser.
- No laser device should be used in any application or situation where life or property is at risk in event of device failure.
- Specifications are subject to change without notice. Ensure that you have the latest specification by contacting us prior to purchase or use of the product.

*\* For reference only. Contents above are subject to change without notice.*

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Laser Diodes](#) category:*

*Click to view products by [Laser Components](#) manufacturer:*

Other Similar products are found below :

[PLT5 520EA P](#) [PLT3 520D](#) [905D1S03UA](#) [905D1S09UA](#) [905D1S3J03UA](#) [905D1S3J09UA](#) [ADL-63054SL](#) [ADL-63301TL](#) [ADL-63V0ANP](#)  
[ADL-65055TL](#) [ADL-65074TA4](#) [ADL-65074TL-1](#) [ADL-65075SL](#) [ADL-65075TA4](#) [ADL-65104TA4](#) [ADL-65104TL](#) [ADL-66201TA4](#) [ADL-](#)  
[66505TL](#) [ADL-66801TL](#) [ADL-78051TL](#) [ADL-78101TL](#) [ADL-83Z01TL](#) [ADL-83Z51TL](#) [ADL-85051TL](#) [ADL-85301TL](#) [ADL-85501TL](#)  
[PLT3 450C](#) [LCU632051A](#) [LCU670561A](#) [HFE4081-321](#) [OPV315YBT](#) [PLT5 450B](#) [ADL-63054TL](#) [ADL-63102TL-3](#) [ADL-63153TL](#) [ADL-](#)  
[65103TL](#) [ADL-66201TL](#) [PLT5 510](#) [LCU66A051A](#) [SPL LL90\\_3](#) [ADL-65075TL](#) [DFB-1310-10LR-LCA](#) [FP-1310-4I-LCB](#) [HFE4192-582](#)  
[FP-1310-5I-50SMF-FCAPC](#) [PL 450B](#) [PL 520\\_B1](#) [PLPT5 450KA](#) [PLPT5 447KA](#) [PLPT9 450LA\\_E](#)