

Mini IR Thermometer

 **Mini size design**
For the ultimate in convenience and portability

Features:

- Temperature range from -34 to 446°F (-33 to 230°C)
- Economical mini size design for convenience
- Automatic Data Hold when measure button is released
- Max Hold or Min Hold
- Lock feature for continuous scanning
- Fixed emissivity covers 90% of surface applications
- Auto power off
- Complete with CR2032 3V battery

Applications:

- Measure hot spots in electrical panels and equipment
- In Process temperature measurements
- Measure surface temperature of objects that are unsafe to contact
- Measure surface temperature of objects that hard to reach



Convenient Mini size

Specifications	
Range:	-34 to 446°F (-33 to 230°C)
Basic Accuracy:	±(2.0%rdg) or ±4°F/±2°C
Max. Resolution:	0.1°F/°C
Emissivity:	0.95 fixed
Field of View (Distance to Target):	1:1
Dimensions:	3 x 1.6 x 0.7" (75 x 40 x 18mm)
Weight:	1.5oz (43g)

Ordering Information:

IR100Mirco IR Thermometer



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Environmental Test Equipment](#) category:

Click to view products by [Extech](#) manufacturer:

Other Similar products are found below :

[CW40](#) [F150C10E3DRT](#) [F150LTC20](#) [F150CD10E2](#) [F150L75](#) [F150LRS](#) [S-11](#) [FLUKE-LDG](#) [382153](#) [FM100](#) [RH210](#) [382253](#) [MO290-P](#)
[GEO-CABLE-REEL-50M](#) [T197914](#) [RD300-L](#) [IR11BD](#) [IR11GM](#) [IR12GM](#) [IR21BD](#) [IR31CE](#) [IR32BC](#) [IR33BC](#) [MP7217TC](#) [NGM-1](#) [SGX-](#)
[7NH3](#) [UT381](#) [F150-SLC50](#) [AW-CO-1000](#) [AW-NmHc-100](#) [3.000.401](#) [AX-7535](#) [CS-9S6SS-A](#) [P 2800 A](#) [P 2801](#) [P 2802](#) [P 5039](#) [P 5130](#) [P](#)
[5055](#) [P 5060](#) [P 5065](#) [P 5086](#) [P 5090](#) [P 5110](#) [P 5115](#) [P 5135](#) [P 5140](#) [P 5145](#) [P 5150](#) [P 5160](#)