

Data Sheet

RF TERMINATION

Type 6500_N-50-2/199_N

Description

Precision Termination, Low Power



Product Configuration

Connector N-precision jack (female)
Interface standards IEC 60169-16_MIL-STD-348A/304_CECC 22210

Technical Data

Electrical Data

Nominal Impedance 50 Ω
Frequency range 0 to 18 GHz
Frequency sub range DC to 4 GHz 4 to 8 GHz 8 to 12.4 GHz 12.4 to 18 GHz
VSWR max. 1.03 1.04 1.05 1.06
Power rating 2 Watt average power up to 25 °C ambient temperature, linearly derated to 1 Watt at 125 °C ambient temperature.
1000 Watt peak power , 5 μ s pulse, 0.05 % duty cycle

Mechanical Data

Weight 0.054 kg

Environmental Data

Operating temperature -65 °C to 125 °C
2011/65/EU (RoHS) compliant

Material Data

Piece Part	Material	Surface Plating
Centre contact	Copper Beryllium Alloy	Gold Plating
Outer contact	Stainless Steel	Passivated (Plating)
Body	Stainless Steel	Passivated (Plating)

Related Documents

Outline drawing DOU-00120722

Ordering Information

Single Packaging 6500_N-50-2/199_NE
Packaging

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [RF Terminators](#) category:

Click to view products by [Huber & Suhner](#) manufacturer:

Other Similar products are found below :

[M39030/3-09S](#) [M39030/3-01S](#) [M39030/3-04N](#) [M39030/3-11N](#) [M39030/3-11S](#) [TNA2-50](#) [TNGFL1-1-78](#) [R4042N5000](#) [32S17B-1.0E3](#)
[28S1ER-001N5](#) [NF-C-1\(40\)](#) [53S1RR-001N3](#) [142275](#) [56S1RR-001N4](#) [18S15R-0.5E3](#) [65_BNC-50-0-7/133_NE](#) [71S1RR-001N4](#) [02S17R-](#)
[001D3](#) [6500.19.A](#) [R404240120](#) [HT-50-1\(40\)](#) [NF-A-PJ-1\(40\)](#) [R404260000](#) [NF-TMJ-P\(50\)](#) [HT-10-2](#) [000-1075](#) [DCA-17-01](#) [27-9245](#)
[M85049/124-13N](#) [R4041D1000](#) [1-221629-6](#) [SF8015-6007](#) [R4041D2121](#) [R4041D2000](#) [R4041D1121](#) [65010_N-50-1/199_NE](#) [65_N-75-0-](#)
[11/133_NE](#) [SF8016-6404](#) [6550.17.AA](#) [65_N-50-0-51/113_NE](#) [65_BNC-50-0-2/133_NE](#) [6560.41.AA](#) [65_QMA-50-0-4/111_NE](#) [65_N-50-0-](#)
[1/133_NE](#) [65002_N-50-1/122_NE](#) [65_SMB-50-0-31/111_NE](#) [65_BNC-50-0-6/113_NE](#) [2702702](#) [1100.19.0001](#) [6701.01.B](#)