

MA130 Mini 200A AC Clamp Meter



Easy-to-use pocket-sized mini clamp meter allows measurements in tight locations. Jaw opening fits conductors up to 300MCM. Manual ranging Current measurements with three ranges to choose from. Features data hold to freeze reading on display and Max hold to record maximum Current reading. Bright backlit display allows user to easily view in dimly lit areas.



Features

- Mini pocket-sized design with backlit LCD display and 0.6" (16mm) jaw size fits conductors up to 300MCM
- CAT III - 300V, CAT II-600V ratings
- Data Hold freezes reading on display
- Max Hold displays maximum reading
- Large LCD with backlit feature for viewing in dimly lit area
- Auto Power Off
- Complete with two AAA batteries

Specifications	Range	Max Resolution	Basic Accuracy
AC Current	2.000A	1mA	±(4% + 30d)
	20.00A	10mA	
	200.0A	100mA	
Dimensions	6.2x2.4x1.3" (158x60x33.5mm)		
Weight	6oz (170g)		

Ordering

MA130 Mini 200A AC Clamp Meter



UPC Code: 793950371305

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Clamp Multimeters & Accessories](#) category:

Click to view products by [Extech](#) manufacturer:

Other Similar products are found below :

[FLUKE 1630-2](#) [ZAPDUMOD-03](#) [ZARKMS-01-99](#) [UT233](#) [TESTO 770-3](#) [0590 7703](#) [AX-3550](#) [AX-M266C](#) [BM079](#) [BM089](#) [BM157](#)
[BM162](#) [BM197](#) [KEW2210R](#) [FLUKE 80I-110S](#) [FLUKE A3002FC](#) [FLUKE I200](#) [FLUKE I200S](#) [FLUKE I3000FLEX-24](#) [FLUKE I310S](#)
[CIE600](#) [TESTO 770-2](#) [0590 7702](#) [34194A](#) [KEW2433R](#) [KEW8112](#) [FLUKE 772](#) [380976-K](#) [MA3110](#) [MA440](#) [MA443](#) [MA445](#) [FLUKE-374](#)
[FC](#) [TA74](#) [AMP-320](#) [CM55](#) [CM46](#) [I200](#) [ACD-6 PRO](#) [FLUKE-1630-2FC](#) [CM44](#) [CM42](#) [FLK-A3000 FC](#) [FLUKE-376 FC](#) [MA610](#) [EA30-](#)
[NIST](#) [F201](#) [F205](#) [MA193 \(250 MM\)](#) [DIGIFLEX 4000A 350MM](#) [DIGIFLEX 400A 170MM](#) [DIGIFLEX 400A 250MM](#)