

Mini IR Thermometer

Compact thermometer measures up to 630°F (332°C)

With built-in laser pointer that identifies target area and improves aim

Features:

- Backlighting illuminates display for taking measurements at night or in areas with low background light levels
- Automatic Data Hold when trigger released
- Min/Max Hold
- Fixed 0.95 emissivity covers 90% of surface applications
- Auto power off
- Complete with 9V battery and case



Ideal for automotive applications



Test for temperature in heating systems



Check building for insufficient insulation



Convenient carrying case included

Specifications	
Range	-4 to 630°F (-20 to 332°C)
Basic Accuracy	±2% of reading +4°F/2°C
Max. Resolution	0.1°F/°C
Emissivity	0.95 fixed
Field of View (Distance to Target)	8:1
Dimensions	3.2 x 1.6 x 6.3" (82x41.5x160mm)
Weight	6.3oz (180g)

Ordering Information:

IR400Mini IR Thermometer (630°F/332°C)



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Environmental Test Equipment](#) category:

Click to view products by [Extech](#) manufacturer:

Other Similar products are found below :

[CW40](#) [F150C10E3DRT](#) [F150LTC20](#) [F150CD10E2](#) [F150L75](#) [F150LRS](#) [S-11](#) [FLUKE-LDG](#) [382153](#) [FM100](#) [RH210](#) [382253](#) [MO290-P](#)
[GEO-CABLE-REEL-50M](#) [T197914](#) [RD300-L](#) [IR11BD](#) [IR11GM](#) [IR12GM](#) [IR21BD](#) [IR31CE](#) [IR32BC](#) [IR33BC](#) [MP7217TC](#) [NGM-1](#) [SGX-](#)
[7NH3](#) [UT381](#) [F150-SLC50](#) [AW-CO-1000](#) [AW-NmHc-100](#) [3.000.401](#) [AX-7535](#) [CS-9S6SS-A](#) [P 2800 A](#) [P 2801](#) [P 2802](#) [P 5039](#) [P 5130](#) [P](#)
[5055](#) [P 5060](#) [P 5065](#) [P 5086](#) [P 5090](#) [P 5110](#) [P 5115](#) [P 5135](#) [P 5140](#) [P 5145](#) [P 5150](#) [P 5160](#)