PRODUCT DATASHEET

**CFM/CMM Thermo-Anemometer** with IR Temperature

## **Built-in IR Thermometer**

Measures non-contact surface temperatures of objects unsafe or difficult to reach

## **Features:**

- InfraRed Thermometer measures remote surface temperatures to 932°F (500°C) with 30:1 distance to spot ratio and Laser pointer
- Simultaneous display of Air Flow in CFM/CMM or Air Velocity plus Ambient Temperature
- Easy to set Area dimensions are stored in the meters internal memory for the next power on
- · Large (9999 count) LCD backlit display
- 20 point average for air flow
- USB port includes software
- Includes Windows® compatible software with cable, vane sensor with 3.9ft (120cm) cable, hard carrying case, and 9V battery









Patented non-contact InfraRed Thermometer technology built into a Thermo-Anemometer is perfect for HVAC applications.



USB port includes PC Software

Specifications	Range	Accuracy
IR Temperature (non-contact)	-58 to 932°F (-50 to 500°C)	±2%
ft/min	80 to 5900 ft/min	±3%
m/s	0.4 to 30.00 m/s	±3%
km/h	1.4 to 108.0 km/h	±3%
MPH	0.9 to 67.0 MPH	±3%
knots	0.8 to 58.0 knots	±3%
Temperature	14 to 140°F (-10 to 60°C)	±4°F (2°C)
CFM/CMM	0 to 999900	
Dimensions	8x3x1.9" (203x75x50mm)	
Weight	9.8oz (280g)	

## **Ordering Information:**

HD300 ......CFM/CMM Thermo-Anemometer with IR Temperature

HD300-NIST ...HD300 with Calibration Traceable to NIST.

TR100 .....Tripod



## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Environmental Test Equipment category:

Click to view products by Extech manufacturer:

Other Similar products are found below:

CW40 F150C10E3DRT F150LTC20 F150CD10E2 F150L75 F150LRS S-11 FLUKE-LDG 382153 FM100 RH210 382253 MO290-P

GEO-CABLE-REEL-50M T197914 RD300-L IR11BD IR11GM IR12GM IR21BD IR31CE IR32BC IR33BC MP7217TC NGM-1 SGX
7NH3 UT381 F150-SLC50 AW-CO-1000 AW-NmHc-100 3.000.401 AX-7535 CS-9S6SS-A P 2800 A P 2801 P 2802 P 5039 P 5130 P

5055 P 5060 P 5065 P 5086 P 5090 P 5110 P 5115 P 5135 P 5140 P 5145 P 5150 P 5160