

Mini IR Thermometer

Compact size

Convenient portable size with wide temperature range measuring up to 1200°F (650°C)

Features:

- Compact thermometer measures temperature from -58 to 1200°F (-50 to 650°C) with 0.1° resolution up to 999.9°
- Adjustable High/Low setpoints with audible alarm alerts user when temperature exceeds the programmed setpoints
- · Adjustable emissivity for better accuracy on different surfaces
- Built-in laser pointer identifies target area
- · Backlighting illuminates display for taking measurements at night or in areas with low background light levels
- 12:1 distance to target ratio
- Data Hold and Min/Max
- Overrange indicator
- Auto power off
- Complete with 9V battery and pouch case



Max hold indicates and holds the peak temperature for easy identification of hot spots



Specifications	
Range	-25 to 1200°F (-50 to 650°C)
Basic Accuracy	\pm (1% of rdg + 2°F/1°C)
Max. Resolution	0.1°F/°C; 1°F/°C
Emissivity	0.10 to 1.00 adjustable
Repeatability	±0.5% or ±1.8°F/°C
Field of View (Distance to Target)	12:1
Dimensions	3.2 x 1.6 x 6.3" (82 x 42 x 160mm)
Weight	6.4oz (180g)

Ordering Information:

42510AMini IR Thermometer 1200°F (650°C), 12:1 42510A-NIST42510A with NIST Certificate



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Environmental Test Equipment category:

Click to view products by Extech manufacturer:

Other Similar products are found below:

CW40 F150C10E3DRT F150LTC20 F150CD10E2 F150L75 F150LRS S-11 FLUKE-LDG 382153 FM100 RH210 382253 MO290-P

GEO-CABLE-REEL-50M T197914 RD300-L IR11BD IR11GM IR12GM IR21BD IR31CE IR32BC IR33BC MP7217TC NGM-1 SGX
7NH3 UT381 F150-SLC50 AW-CO-1000 AW-NmHc-100 3.000.401 AX-7535 CS-9S6SS-A P 2800 A P 2801 P 2802 P 5039 P 5130 P

5055 P 5060 P 5065 P 5086 P 5090 P 5110 P 5115 P 5135 P 5140 P 5145 P 5150 P 5160