



Heavy Duty Hot Wire Thermo-Anemometer

Telescoping probe is designed to fit into small openings And measures airflow down to 40ft/min (0.2m/s)

Features:

- Telescoping probe is ideal for measuring in HVAC ducts and other small vents; extends up to 7ft (2.1m) maximum length with cable
- Built-in RS-232 PC serial interface for connection to PC
- Extra large 1.4" (36mm) dual LCD display
- MAX/MIN, Data Hold
- Complete with telescoping probe with cable, six AAA batteries and protective holster.
 NOTE: AC Adaptor not available for this model
- Optional Windows[®] compatible Data Acquisition Software and serial cable enable user to display and capture readings on a PC, with adjustable sample rate and alarms





Specifications	Resolution	Basic Accuracy
Air Velocity		
0.2 to 20m/s	0.1m/s	±3%
40 to 3940ft/min	1ft/min	
0.5 to 45MPH	0.1MPH	
1.0 to 38.8knots	0.1knots	
0.7 to 72km/h	0.1km/h	
Temperature & Windchill		
32 to 122°F	0.1°	±1.5°F
0 to 50°C	0.1°	±0.8°C
Dimensions	7 x 2.9 x 1.3" (178 x 74 x 33mm)	
Weight	17oz (482g)	

Ordering Information:

407123.....Heavy Duty Hot Wire Thermo-Anemometer 407123-NISTHeavy Duty Hot Wire Thermo-Anemometer w/ Calibration Traceable to NIST 407001Data Acquisition PC Software and Serial Cable 407001-USBUSB Adaptor for 407001



www.extech.com

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Environmental Test Equipment category:

Click to view products by Extech manufacturer:

Other Similar products are found below :

 CW40
 F150C10E3DRT
 F150LTC20
 F150CD10E2
 F150L75
 F150LRS
 S-11
 FLUKE-LDG
 382153
 FM100
 RH210
 382253
 MO290-P

 GEO-CABLE-REEL-50M
 T197914
 RD300-L
 IR11BD
 IR11GM
 IR21BD
 IR31CE
 IR32BC
 IR33BC
 MP7217TC
 NGM-1
 SGX

 7NH3
 UT381
 F150-SLC50
 AW-CO-1000
 AW-NmHc-100
 3.000.401
 AX-7535
 CS-9S6SS-A
 P 2800 A
 P 2801
 P 2802
 P 5039
 P 5130
 P

 5055
 P 5060
 P 5065
 P 5086
 P 5090
 P 5115
 P 5135
 P 5140
 P 5145
 P 5150
 P 5160