RAMO 30 T - Pushbutton FLEXLAB without lens, white, M8

1.11.010.201/0200





 \mathbb{R}

General information	
Form	FLEXLAB without lens
Color of front ring	stainless steel
Form of collar	round
Color lens	white
Dimensions	
Mounting hole	30.3 mm
Mechanical design	
Contact	momentary, 1 NO
Contact materials	gold
Mounting	ring nut
Terminals	<u>M8</u>
Reverse polarity protection	yes
Labeling	individually with FLEXLAB
Output	1 NO, PNP
Torque for nut ring	<u>1.2 Nm</u>
Mechanical characteristics	
Operating force F1 (+/-20 %)	<u>5 N</u>
Electrical characteristics	
Rated voltage min.	DC 0.02 V V
Rated current min.	 0.01 mA
Rated voltage max.	DC 35 V
Rated current max.	 100 mA
Rated power max.	1 W (ohmsche Last) W
LED power supply	DC 24 V +- 20% / 10 mA +- 20%
Other specifications	
Ambient temp. operating min.	-40 °C
Ambient temp. operating max.	+70 °C
B10	500,000 cycle
Degree of protection from front side	IP 66, IP 67, IP 69K
Degree of protection from rear side	IP 66 (je nach verwendetem Stecker IP 67 oder IP 69K)
Environmental restistance	acc. to IEC 60068-2-14, -30, -33 and -78
Operating life cycles	250,000
ROHS compliant	yes
REACH compliant	yes

Technical data are approximate and intended solely for general orientation in the selection of a product. Subject to modifications and errors. Images and other graphics may only be similar. For more information, refer to www.rafi.de chapter Imprint / Data Protection.







Technical data are approximate and intended solely for general orientation in the selection of a product. Subject to modifications and errors. Images and other graphics may only be similar. For more information, refer to www.rafi.de chapter Imprint / Data Protection.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Pushbutton Switches category:

Click to view products by Rafi manufacturer:

Other Similar products are found below :

LW1L-M1C10V-A LW2L-A1C20M-GD LW2L-M1C20M-A 60324L M7E-HRN2 67021K512 67081K512X 701PB580 719-5504-000 MDPSSGLFS 810KSV30B FLT 2U EE 01A MML21KA3ABK MML23KA3AC05K-001 MML23KW3AA01W 8418K2 8646AB6X718UL 8646ABUL FSDWH 9001KXRK 9001T8BK 9533CD4+U574+U4922 1203MRA A22EM01S A595 1202A6 12037A2ULCSA 1203A2UL ABD122N-B 1211390004 ABN111-Y ABN400-R 1211500044 1211580012 1212MRA 1232A6NF RA3CSH6A 1241.1183.7047 1241.2511 1241.3428 1223A2ULCSA 1223MRA 1232AX2119 1241.1183.8000 1241.1183.8029 1241.2506 1241.2606 12MA6 1301940184 RELBARF6X10(PLASTIC)