


RAMO 22 T - Pushbutton, white, collar round, M12

1.10.011.001/0221




Form flush Color of front ring black Form of collar round Color lens white Dimensions Mounting hole 22.3 mm	NO
Form of collar round Color lens white Dimensions Mounting hole 22.3 mm	NO
Color lens white Dimensions Mounting hole 22.3 mm	NO
Dimensions Mounting hole 22.3 mm	NO
Mounting hole 22.3 mm	NO
Mounting hole 22.3 mm	NO
	NO
	NO
Mechanical design	NO
Contact momentary, 1	
Contact materials gold	
Mounting ring nut	
Terminals M12	
Reverse polarity protection yes	
Labeling individually w	ith FLEXLAB
Torque for nut ring 1.2 Nm	
Mechanical characteristics	
Operating force F1 (+/-20 %) 5 N	
<u> </u>	
Electrical characteristics	
Rated voltage min. DC 0.02 V V	
Rated current min. 0.01 mA	
Rated voltage max. DC 35 V	_
Rated current max. 100 mA	
Rated power max. 1 W (ohmsch	
LED power supply DC 24 V +- 20	0% / 10 mA +- 20%
Other specifications	
Ambient temp. operating min40 °C	
Ambient temp. operating max. +70 °C	
B10 500,000 cycle)
Degree of protection from front side IP 66, IP 67, I	
Degree of protection from rear side IP 66 (je nach	verwendetem Stecker IP 67 oder IP 69K)
Environmental restistance acc. to IEC 60	0068-2-14, -30, -33 and -78
Operating life cycles 250,000	
ROHS compliant yes	
REACH compliant yes	





Einbauöffnung nach IEC 60947-5-1



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Pushbutton Switches category:

Click to view products by Rafi manufacturer:

Other Similar products are found below:

LW1L-M1C10V-A LW2L-A1C20M-GD LW2L-M1C20M-A 60324L M7E-HRN2 67021K512 67081K512X 701PB580 719-5504-000

MDPSSGLFS 810KSV30B FLT 2U EE 01A MML21KA3ABK MML23KA3AC05K-001 MML23KW3AA01W 8418K2 8646AB6X718UL

8646ABUL FSDWH 9001KXRK 9001T8BK 9533CD4+U574+U4922 1203MRA A22EM01S A595 1202A6 12037A2ULCSA 1203A2UL

ABD122N-B 1211390004 ABN111-Y ABN400-R 1211500044 1211580012 1212MRA 1232A6NF RA3CSH6A 1241.1183.7047

1241.2511 1241.3428 1223A2ULCSA 1223MRA 1232AX2119 1241.1183.8000 1241.1183.8029 1241.2506 1241.2606 12MA6

1301940184 RELBARF6X10(PLASTIC)