


Central
 Semiconductor Corp.
**Central
 Semiconductor Corp.**
**Central™
 Semiconductor Corp.**
 145 Adams Avenue
 Hauppauge, New York 11788



2N6428
 2N6429

NPN SILICON TRANSISTOR

JEDEC TO-92 CASE (EBC)

DESCRIPTION

The CENTRAL SEMICONDUCTOR 2N6428, 2N6429 types are NPN Silicon Transistors manufactured by the epitaxial planar process, designed for high gain amplifier applications.

MAXIMUM RATINGS ($T_A = 25^\circ\text{C}$)

	<u>SYMBOL</u>	<u>2N6428</u>	<u>2N6429</u>	<u>UNITS</u>
Collector-Base Voltage	V_{CB0}	60	55	V
Collector-Emitter Voltage	V_{CE0}	50	45	V
Emitter-Base Voltage	V_{EBO}	6.0		V
Collector Current	I_C	200		mA
Power Dissipation	P_D	625		mW
Power Dissipation ($T_C = 25^\circ\text{C}$)	P_D	1.5		W
Operating and Storage				
Junction Temperature	T_J, T_{stg}	-65 to +150		$^\circ\text{C}$
Thermal Resistance	Θ_{JA}	200		$^\circ\text{C}/\text{W}$
Thermal Resistance	Θ_{JC}	83.3		$^\circ\text{C}/\text{W}$

ELECTRICAL CHARACTERISTICS ($T_A = 25^\circ\text{C}$ unless otherwise noted)

<u>SYMBOL</u>	<u>TEST CONDITIONS</u>	<u>2N6428</u>		<u>2N6429</u>		<u>UNITS</u>
		<u>MIN</u>	<u>MAX</u>	<u>MIN</u>	<u>MAX</u>	
I_{CBO}	$V_{CB} = 30\text{V}$		10		10	nA
I_{CEO}	$V_{CE} = 30\text{V}$		25		25	nA
I_{EBO}	$V_{BE} = 5.0\text{V}$		10		10	nA
BV_{CBO}	$I_C = 100\mu\text{A}$	60		55		V
BV_{CEO}	$I_C = 1.0\text{mA}$	50		45		V
$V_{CE(SAT)}$	$I_C = 10\text{mA}, I_B = 0.5\text{mA}$		0.20		0.20	V
$V_{CE(SAT)}$	$I_C = 100\text{mA}, I_B = 5.0\text{mA}$		0.60		0.60	V
$V_{BE(ON)}$	$V_{CE} = 5.0\text{V}, I_C = 1.0\text{mA}$	0.56	0.66	0.56	0.66	V
h_{FE}	$V_{CE} = 5.0\text{V}, I_C = 10\mu\text{A}$	250		500		
h_{FE}	$V_{CE} = 5.0\text{V}, I_C = 100\mu\text{A}$	250	650	500	1250	
h_{FE}	$V_{CE} = 5.0\text{V}, I_C = 1.0\text{mA}$	250		500		
h_{FE}	$V_{CE} = 5.0\text{V}, I_C = 10\text{mA}$	250		500		
f_T	$V_{CE} = 5.0\text{V}, I_C = 1.0\text{mA}, f = 100\text{MHz}$	100	700	100	700	MHz
C_{ob}	$V_{CB} = 10\text{V}, I_E = 0, f = 1.0\text{MHz}$		3.0		3.0	pF
C_{ib}	$V_{BE} = 0.5\text{V}, I_C = 0, f = 1.0\text{MHz}$		8.0		8.0	pF
h_{ie}	$V_{CE} = 5.0\text{V}, I_C = 1.0\text{mA}, f = 1.0\text{kHz}$	3.0	30	6.0	60	$\text{k}\Omega$
h_{re}	$V_{CE} = 5.0\text{V}, I_C = 1.0\text{mA}, f = 1.0\text{kHz}$	2.0	20	5.0	50	$\times 10^{-4}$
h_{fe}	$V_{CE} = 5.0\text{V}, I_C = 1.0\text{mA}, f = 1.0\text{kHz}$	200	800	400	1600	
h_{oe}	$V_{CE} = 5.0\text{V}, I_C = 1.0\text{mA}, f = 1.0\text{kHz}$	5.0	50	10	100	μmhos

145 Adams Avenue, Hauppauge, NY 11788 USA
 Tel: (631) 435-1110 • Fax: (631) 435-1824



OUTSTANDING SUPPORT AND SUPERIOR SERVICES

PRODUCT SUPPORT

Central's operations team provides the highest level of support to insure product is delivered on-time.

- Supply management (Customer portals)
- Inventory bonding
- Consolidated shipping options
- Custom bar coding for shipments
- Custom product packing

DESIGNER SUPPORT/SERVICES

Central's applications engineering team is ready to discuss your design challenges. Just ask.

- Free quick ship samples (2nd day air)
- Online technical data and parametric search
- SPICE models
- Custom electrical curves
- Environmental regulation compliance
- Customer specific screening
- Up-screening capabilities
- Special wafer diffusions
- PbSn plating options
- Package details
- Application notes
- Application and design sample kits
- Custom product and package development

REQUESTING PRODUCT PLATING

1. If requesting Tin/Lead plated devices, add the suffix " TIN/LEAD" to the part number when ordering (example: 2N2222A TIN/LEAD).
2. If requesting Lead (Pb) Free plated devices, add the suffix " PBFREE" to the part number when ordering (example: 2N2222A PBFREE).

CONTACT US

Corporate Headquarters & Customer Support Team

Central Semiconductor Corp.
145 Adams Avenue
Hauppauge, NY 11788 USA
Main Tel: (631) 435-1110
Main Fax: (631) 435-1824
Support Team Fax: (631) 435-3388
www.centrasemi.com

Worldwide Field Representatives:
www.centrasemi.com/wwreps

Worldwide Distributors:
www.centrasemi.com/wwdistributors

For the latest version of Central Semiconductor's **LIMITATIONS AND DAMAGES DISCLAIMER**, which is part of Central's Standard Terms and Conditions of sale, visit: www.centrasemi.com/terms

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Bipolar Transistors - BJT category](#):

Click to view products by [Central Semiconductor manufacturer](#):

Other Similar products are found below :

[619691C](#) [MCH4017-TL-H](#) [MJ15024/WS](#) [MJ15025/WS](#) [BC546/116](#) [BC556/FSC](#) [BC557/116](#) [BSW67A](#) [HN7G01FU-A\(T5L,F,T](#)
[NJVMJD148T4G](#) [NSVMMBT6520LT1G](#) [NTE187A](#) [NTE195A](#) [NTE2302](#) [NTE2330](#) [NTE2353](#) [NTE316](#) [IMX9T110](#) [NTE63](#) [NTE65](#)
[C4460](#) [SBC846BLT3G](#) [2SA1419T-TD-H](#) [2SA1721-O\(TE85L,F\)](#) [2SA1727TLP](#) [2SA2126-E](#) [2SB1202T-TL-E](#) [2SB1204S-TL-E](#) [2SC5488A-](#)
[TL-H](#) [2SD2150T100R](#) [SP000011176](#) [FMC5AT148](#) [2N2369ADCSM](#) [2SB1202S-TL-E](#) [2SC2412KT146S](#) [2SC4618TLN](#) [2SC5490A-TL-H](#)
[2SD1816S-TL-E](#) [2SD1816T-TL-E](#) [CMXT2207 TR](#) [CPH6501-TL-E](#) [MCH4021-TL-E](#) [BC557B](#) [TTC012\(Q\)](#) [BULD128DT4](#) [JANTX2N3810](#)
[Jantx2N5416](#) [US6T6TR](#) [KSF350](#) [068071B](#)