Data Sheet

RF TERMINATION Type 6500_N-50-1/199_N

Description

Precision Termination, Low Power



Product Configuration N-precision plug (male) Connector IEC 60169-16_MIL-STD-348A/304_CECC 22210 Interface standards **Technical Data Electrical Data** 50 Ω Nominal Impedance 0 to 18 GHz Frequency range Frequency sub range DC to 4 GHz 4 to 8 GHz 8 to 12.4 GHz 12.4 to 18 GHz VSWR max. 1 04 1 05 1 06 1 03 Power rating 2 Watt average power up to 25 °C ambient temperature, linearly derated to 1 Watt at 125 °C ambient temperature. 1000 Watt peak power , 5 µs pulse, 0.05 % duty cycle **Mechanical Data** Weight 0.057 kg **Environmental Data** Operating temperature -65 °C to 125 °C 2011/65/EU (RoHS) compliant **Material Data** Piece Part Material Surface Plating Centre contact Copper Beryllium Alloy Gold Plating Outer contact Stainless Steel Passivated (Plating) Passivated (Plating) Body Stainless Steel Coupling nut Stainless Steel Passivated (Plating)

Related Documents

Outline drawing

DOU-00120720

Ordering Information

Single Packaging Packaging 6500_N-50-1/199_NE

HUBER+SUHNER is certified according to ISO 9001, ISO 14001, AS/EN9100, ISO/TS 16949 and IRIS Waiver: Fact and figures herein are for information only and do not represent any warranty of any kind. www.hubersuhner.com

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for RF Terminators category:

Click to view products by Huber & Suhner manufacturer:

Other Similar products are found below :

M39030/3-09S M39030/3-01S M39030/3-04N M39030/3-11N M39030/3-11S TNA2-50 TNGFL1-1-78 R4042N5000 32S17B-1.0E3 28S1ER-001N5 NF-C-1(40) 53S1RR-001N3 142275 56S1RR-001N4 18S15R-0.5E3 65_BNC-50-0-7/133_NE 71S1RR-001N4 02S17R-001D3 6500.19.A R404240120 HT-50-1(40) NF-A-PJ-1(40) R404260000 NF-TMJ-P(50) HT-10-2 000-1075 DCA-17-01 27-9245 M85049/124-13N R4041D1000 1-221629-6 SF8015-6007 R4041D2121 R4041D2000 R4041D1121 65010_N-50-1/199_NE 65_N-75-0-11/133_NE SF8016-6404 6550.17.AA 65_N-50-0-51/113_NE 65_BNC-50-0-2/133_NE 6560.41.AA 65_QMA-50-0-4/111_NE 65_N-50-0-1/133_NE 65002_N-50-1/122_NE 65_SMB-50-0-31/111_NE 65_BNC-50-0-6/113_NE 2702702 1100.19.0001 6701.01.B